Catalog Number:	U5852-RL-100
Item Description:	200A 4T RT MTR MAIN OH
UPC Code:	784572512757



Brand Name:	Milbank
Type:	Ring Type Meter Socket
Application:	Meter Socket With Main
Standard:	UL Listed
Voltage Rating:	Up to 240 Volts Alternating Current
Amperage Rating:	200 Continuous Ampere
Phase:	1 Phase
Frequency Rating:	60 Hertz
Number Of Cutouts:	1
Cutout Size:	100 Ampere Main Breaker
Cable Entry:	Overhead
Terminal:	Lay in Line Side and Single Mechanical Load Side
Mounting:	Surface Mount
Enclosure:	Type 3R, G90 Galvanized Steel with Powder Coat Finish

Additional Specifications:

Number of Jaws:4 Terminal

Hub Opening and Closing Plates:Small Hub Opening

Hub Opening and Closing Plates:Small Hub Opening


Hub Opening and Closing Plates:Small Hub Opening


Hub Opening and Closing Plates:Small Hub Opening


Hub Opening and Closing Plates:Small Hub Opening


Utility requirements may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must always be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

FEATURE TABLE		
ITEM	QTY	DESCRIPTION
A	6	U/L MNTG.EMBOSS
B	1	¼ SOLID K.O.
C	1	¼, ½ CONC. K.O.
D	4	1, 1¼, 1½, 2, 2½ CONC. K.O.









MILBANK
ENERGY AT WORK

Version:

1

All dimensions are +/- 1/16".
Drawing views are not to scale.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.