



Catalog Number: UCSSP3433-O  
Item Description: 20A 13T RT TS PROV UG  
UPC Code: 784572630451




Brand Name: Milbank  
Type: Ring Type Meter Socket  
Application: Meter Socket  
Standard: UL Listed  
Voltage Rating: 600 Volts Alternating Current  
Amperage Rating: 20 Continuous Ampere  
Phase: 3 Phase  
Frequency Rating: 60 Hertz  
Number Of Cutouts: 0  
Cable Entry: Underground  
Terminal: Single Mechanical Line Side and Single Mechanical Load Side  
Mounting: Surface Mount  
Enclosure: Type 3R, 304 Stainless Steel with Powder Coat Finish

Additional Specifications: Number of Jaws:13 Terminal  
Hub Opening and Closing Plates:Plain Top  
Hub Opening and Closing Plates:Plain Top  
Hub Opening and Closing Plates:Plain Top  
Hub Opening and Closing Plates:Plain Top  
Hub Opening and Closing Plates:Plain Top



*Utility requirements may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must always be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.*

| FEATURE TABLE |     |                               |
|---------------|-----|-------------------------------|
| ITEM          | QTY | DESCRIPTION                   |
| A             | 4   | STD. MNTG. EMBOSS             |
| B             | 3   | ½, ¾, 1, 1¼, 1½ CONC. K.O.    |
| C             | 4   | ½, ¾, 1, 1¼, 1½, 2 CONC. K.O. |



Version:

1

All dimensions are +/- 1/16".  
Drawing views are not to scale.  
Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.