



9368-EK

[VIDEO](#)

Product Description

Single gang electrical box for use with nonmetallic sheathed cable

Brand: fiberglassBOX™**Catalog #:** 9368-EK**Carton Quantity:** 100**Carton Weight:** 32 lb.**Height:** 3-1/4 in.**Width:** 2-3/8 in.**Depth:** 3-3/16 in.**Volume:** 18 cu. in.**UPC:** 085339760030**UNSPSC:** 39121308**Country of Origin:** United States of America**Type of Installation:** Old Work**Wall Box****Number of Gangs:** 1

FEATURES

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

APPLICATION

Old work residential construction 2 HR fire resistive walls and ceilings

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C***Fire Resistance Classification in Wall Assemblies 2-Hours or less**

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Beige/tan

ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

MATERIAL

Fiberglass reinforced polyester BMC

Polyvinyl chloride clamps

MOUNTING

Metal ears