



## 9371-FRV

[VIDEO](#)

### Product Description

4" dia. round fixture support box for use with nonmetallic sheathed cable

**Brand:** fiberglassBOX™ - Vapor Seal  
**Catalog #:** 9371-FRV

**Carton Quantity:** 24  
**Carton Weight:** 10 lb.

**Width:** 4 in.  
**Depth:** 2-7/8 in.  
**Volume:** 12 cu. in.

**UPC:** 085339927051  
**UNSPSC:** 39121316  
**Patents:**

**Type of Installation:** Old or New Work  
**Round Ceiling Box**

U.S. Patent No. 6,908,003 B2  
**Country of Origin:** United States of America

### FEATURES

Polyurethane flange for single drywall offset, 1/2" deep base with side cube wiring capacity, fan/fixture screws for joist mounting, machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

### APPLICATION

New and old work residential construction 2 HR fire resistive walls and ceilings (70 lbs. fan support and 110 lbs. fixture support), air-sealed electrical fan support box for Energy Star homes

### STANDARDS

ANSI / UL 514C: File No. E30594



LISTED

NEMA OS 4 - Energy Efficient Air-Sealed Boxes for Electrical Applications



### FIRE CLASSIFICATION

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

#### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

### COLOR

Beige/tan

### MATERIAL

Fiberglass reinforced polyester BMC

### MOUNTING

Bottom mount

### ADDITIONAL MATERIALS

Polyvinyl chloride clamps

Polyurethane flange

Plated carbon steel fasteners

### SUPPORT RATING

110 lbs fixture support and 70 lbs fan support

