



**ALLIED  
MOULDED  
PRODUCTS, Inc.**

222 N Union Street • Bryan, OH 43506  
Ph: (800) 722-2679 • Fx: (800) 237-7269

Email: [sales@alliedmoulded.com](mailto:sales@alliedmoulded.com)  
[www.alliedmoulded.com](http://www.alliedmoulded.com)

## P-643H



### Product Description

Three gang electrical box for use with nonmetallic sheathed cable

**Brand:** flexBOX®  
**Catalog #:** P-643H

**Height:** 3-3/4 in.  
**Width:** 5-13/16 in.  
**Depth:** 3-9/16 in.  
**Volume:** 64 cu. in.  
**Type of Installation:** New Work  
**Wall Box**  
**Number of Gangs:** 3

**Carton Quantity:** 20  
**Carton Weight:** 11 lb.

**UPC:** 085339463030  
**UNSPSC:** 39121308  
**Patents:**  
U.S. Patent No. 6,365,831 B1  
**Country of Origin:** United States of America

### FEATURES

Molded-in splined device holes, leveling ribs

### APPLICATION

New work residential construction 2 HR fire resistive walls

### STANDARDS

ANSI / UL 514C: File No. E30594



### FIRE CLASSIFICATION

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

### COLOR

Black

### ADDITIONAL MATERIALS

Galvanized snap in bracket

### MATERIAL

Polycarbonate

### MOUNTING

Stud face mount steel hanger bracket with 1/2" offset and opposite side drywall tabs