



## SB-CBG

[VIDEO](#)

### Product Description

4" dia. round fixture support box for use with nonmetallic sheathed cable

**Brand:** SLIDERBOX®  
**Catalog #:** SB-CBG

**Width:** 4 in.  
**Depth:** 2-3/4 in.  
**Volume:** 25 cu. in.

**Type of Installation:** Old or New Work  
**Round Ceiling Box**

**Carton Quantity:** 12  
**Carton Weight:** 4 lb.

**UPC:** 085339945079  
**UNSPSC:** 39121316  
**Patents:**  
U.S. Patent No. 7,855,338

**U.S. Patent No. 6,365,831 B1**  
**Country of Origin:** United States of America

### FEATURES

Machine tapped fixture holes, adjustable mounting plate for additional substrate thickness

### APPLICATION

New and old work residential construction 2 HR fire resistive floors and ceilings (50 lbs. fixture support)

### STANDARDS

ANSI / UL 514C: File No. E30594



### FIRE CLASSIFICATION

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

#### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

### COLOR

Beige/tan

### ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

### MATERIAL

Polycarbonate

Carbon steel fasteners

### MOUNTING

Internal screws with adjustable slider plate for substrates 1/2" to 1 5/32"

Galvanized ground strap with plated carbon steel fastener and green plated carbon steel ground screw

### SUPPORT RATING

50 lbs fixture support