


Specialty Standard Grade Receptacles

2-Pole, 3-Wire Grounding
15A, 125V/AC
15A, 250V/AC



FEATURES

- Tamper Resistant versions provide compliance with 2011 NEC® Article 406.12 that states that all receptacles installed in dwelling units must be tamper resistant. 
- Recessed receptacles feature a virtually unbreakable thermoplastic housing and tamper resistant shutters.
- Surface receptacles for use with surface mounted wiring to expand convenience receptacles on solid plaster, brick or concrete walls.
- Floor box assembly includes heavy-duty single receptacle on recessed mounting strap, 18 cu. in steel back box, solid brass cover, gasket and threaded brass closure cap with watertight neoprene rubber "O" ring.
- High impact-resistant thermoplastic face and back body eliminates breakage.
- Double-wipe ground contacts ensure long-term ground retention.
- Tri-combo screws accept Slotted-, Phillips-, and Robertson-head tools for installation flexibility.
- Side wire terminals accept up to #10 AWG solid wire.



TR780

Recessed Receptacles

15A 125V/AC; Side Wire

Description	Color Suffix	Catalog No.
Tamper Resistant NEMA 5-15R Single Receptacle, with Clock Hanger	W	☐ TR775__
Tamper Resistant NEMA 5-15R Duplex Receptacle	W	☐ TR780__

  cULus Listed to UL498 file no. E15058; NOM certified



78

Surface Receptacles

15A 125V/AC NEMA 5-15R or 15A 250V/AC NEMA 6-15R

Description	Color Suffix	Catalog No.	
NEMA 5-15R Duplex Surface Receptacle	B, V	☐ 78__	•
NEMA 6-15R Duplex Surface Receptacle	V	☐ 74__	•

   Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified except 74



TR5797

Floor Box Receptacles

15A 125V/AC; Back & Side Wire

Description	Receptacle Color	Catalog No.	
Tamper Resistant NEMA 5-15R Single Receptacle Brass Floor Box Assembly	Black	☐ TR5797__	•

 cULus Listed to UL498 file no. E15058

Color Ordering Information: For ordering devices, include Cat. No. followed by the color code: B (Brown), V (Ivory), W (White)

Dimensional Information: B-61

Specification Information: Please visit www.cooperwiringdevices.com

 **NAFTA Compliant:** See page F-21