

## Special Use Lampholder Assemblies

Miscellaneous Assemblies  
100W, 120V/AC

### FEATURES

- Utility lampholder features removable threaded reflector.
- Utility lampholder fully adjustable with 360° rotation and 180° angle adjustment.
- Automatic closet light lampholder contains an automatic switch that is activated by opening or closing of hinged or sliding doors.



C386

### Closet Light Lampholder

100W, 120V/AC

| Description   | Color | Catalog No.                   |
|---|-------|-------------------------------|
| 100W, 120V Automatic Closet Light Lampholder on 9' (2.7m) 18-2 SPT-1 Power Cord | Ivory | <input type="checkbox"/> C386 |

## Lampholder Adapters & Accessories

Polarized, Medium Base  
660W, 125V/AC  
660W, 250V/AC

### FEATURES

- Outlets on adapters are 2-wire polarized.
- Pull chain on catalog number 718 controls the bulb socket, side outlets are continually on.



715




758








700


### Socket Adapters

660W 125V/AC or 660W 250V/AC

| Description  | Color or Color Suffix | Catalog No.                    |  |
|--|-----------------------|--------------------------------|---|
| 125V, Converts One Socket to One Socket with Two 250W NEMA 1-15R 2P, 2W Outlets, Pull Chain Switch | B, V                  | <input type="checkbox"/> 718__ | •   |
| 125V, Converts One Socket to One Socket with Two 250W NEMA 1-15R 2P, 2W Outlets, Keyless Switch    | B, V                  | <input type="checkbox"/> 715__ | •   |
| 125V, Converts One Socket to One 125V NEMA 1-15R 2P, 2W Outlet, Keyless Switch                     | B, W                  | <input type="checkbox"/> 758__ |   |
| 125V, Converts One Socket to One 125V NEMA 1-15R 2P, 2W Outlet, Keyless Switch                     | Brown                 | <input type="checkbox"/> 808   | •   |
| 250V, Converts One Socket to Two Sockets, Keyless Switch   | B, W                  | <input type="checkbox"/> 700__ | •   |

   700, 718, 808: Listed to UL496 & UL498, file no. E15055; CSA certified to C22.2, no. 42 & 43; NOM certified (except 808)

  715: cULus Listed to UL496 & UL498, file no. E15055; certified to CSA C22.2, no. 42 & 43; NOM certified

 758: cULus Listed to UL496 & UL498, file no. E136278; certified to CSA C22.2, no. 42 & 43

**Color Ordering Information:** For ordering devices, include Cat. No. followed by the color code if applicable: B (Brown), V (Ivory), W (White)

**Dimensional Information:** B-65

**Specification Information:** Please visit [www.cooperwiringdevices.com](http://www.cooperwiringdevices.com)

 **NAFTA Compliant:** See page F-21