
Industrial grade 50A locking devices

Product description

2-pole, 3-wire grounding
50A, 125V/AC
Non-NEMA, marine grade




Receptacle **Plug**



63CR61



63CR60



63CR70

Marine grade plugs & connectors

Rating A	Rating V/AC	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
50	125	Pro grip nylon	0.44-1.06" (11.1-26.0mm)	Y & BK	☐63CR61EX	☐63CR60EX	•	•
		Armored	0.68-1.13" (17.3-28.6mm)	Stainless steel	☐63CR61		•	•
		Armored	0.68-1.13" (17.3-28.6mm)	Stainless steel		☐63CR60		•

Marine grade receptacles

Rating A	Rating V/AC	Description	Color	Single receptacle		
50	125	Corrosion resistant	BK	☐63CR70	•	•

Accessories for 50A marine grade locking devices

Description	Color suffix	Catalog no.		
Weather protective glass-filled nylon, w/ lift lid cover	BK, CR, GY	☐7788__	•	•
Weather protective diecast aluminum, w/ lift lid cover		☐7770		•
Weather protective boot for 50A armored plug		☐7716		•
Weather protective boot for 50A armored connector		☐7717		•
Weather protective boot for 50A pro grip plug		☐7716EX		•
Weather protective boot for 50A pro grip connector		☐7717EX		•
For 50A armored connector when used w/ hull inlet (NOT California standard)		☐77CR15		•



7788CR Corrosion resistant



7770



7716



7717



7716EX



7717EX



77CR15

Dimensional information:
C-80, C-81

Plug & connector specification information:
50A: C-91

Receptacle specification information:
50A marine: C-91

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: BK (Black), GY (Gray), Y or CR (Yellow)

BK	GY	Y or CR	
(Black)	(Gray)	(Yellow)	(Stainless Steel)

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32