


Complex environment locking devices

Product description

2-pole, 3-wire grounding
20A, 480V/AC
NEMA L8-20



L8-20R

L8-20P

Plugs & connectors


Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	480	L8-20	Watertight	0.36-0.84" (9.1-21.3mm)	Y	□ L820PW	□ L820CW	•	•
			Watertight	0.36-0.84" (9.1-21.3mm)	BK	□ L820PWBK	□ L820CWBK	•	•
			Severe duty	0.38-1.00" (9.7-25.4mm)	Y & BK	□ L820PY	□ L820CY	•	•

Receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.	
20	480	L8-20	Watertight	Y	□ L820RW	•
			Watertight	BK	□ L820RWBK	•



CRL530C



L530RW

Complex environment locking devices

Product description

2-pole, 3-wire grounding
30A, 125V/AC
NEMA L5-30



L5-30R

L5-30P

Plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
30	125	L5-30	Watertight	0.43-1.15" (10.9-29.2mm)	Y	□ L530PW	□ L530CW	•	•
			Watertight	0.43-1.15" (10.9-29.2mm)	BK	□ L530PWBK	□ L530CWBK	•	•
			Severe duty	0.38-1.00" (9.7-25.4mm)	Y & BK	□ L530PY	□ L530CY	•	•
			Safety grip corrosion resistant	0.38-1.00" (9.7-25.4mm)	Y	□ CRL530P	□ CRL530C	•	•

Receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.		
30	125	L5-30	Watertight	Y	□ L530RW	•	•
			Watertight	BK	□ L530RWBK	•	•
			Corrosion resistant	Y	□ CRL530R*	•	•

* UL Listed, CSA certified and Fed Spec

Dimensional information:
D-34-35

Specification information:
Watertight industrial plugs & connectors: D-38
Watertight industrial receptacles: D-39
Severe duty industrial plugs & connectors: D-40
Corrosion resistant: D-41

Color information:

BK (Black), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32