


Complex environment locking devices

Product description

3-pole, 3-wire non-grounding
20A, 125/250V/AC
NEMA L10-20



L10-20R L10-20P



L1020CY



L1120PW

Plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	125/ 250	L10-20	Watertight	0.43-1.15" (10.9-29.2mm)	Y	□ L1020PW	□ L1020CW	•	•
			Watertight	0.43-1.15" (10.9-29.2mm)	BK	□ L1020PWBK	□ L1020CWBK	•	•
			Severe duty	0.38-1.00" (9.7-25.4mm)	Y & BK	□ L1020PY	□ L1020CY	•	•


Receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.	
20	125/ 250	L10-20	Watertight	Y	□ L1020RW	•
			Watertight	BK	□ L1020RWBK	•

Complex environment locking devices

Product description

3-pole, 3-wire non-grounding
20A, 3Ø 250V/AC
NEMA L11-20



L11-20R L11-20P

3Ø plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	250	L11-20	3Ø watertight	0.43-1.15" (10.9-29.2mm)	Y	□ L1120PW	□ L1120CW	•	•
			3Ø watertight	0.43-1.15" (10.9-29.2mm)	BK	□ L1120PWBK	□ L1120CWBK	•	•
			3Ø severe duty	0.38-1.00" (9.7-25.4mm)	Y & BK	□ L1120PY	□ L1120CY	•	•

3Ø receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.	
20	250	L11-20	3Ø watertight	Y	□ L1120RW	•
			3Ø watertight	BK	□ L1120RWBK	•

Dimensional information:
D-34-35

Specification information:
Watertight industrial plugs & connectors: D-38
Watertight industrial receptacles: D-39
Severe duty industrial plugs & connectors: D-40

Color information:

BK (Black), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.

 Indicates NAFTA compliant - Page Q-32

 RoHS compliant - Page Q-32