

Locking devices


Complex environment locking devices

Product description

3-pole, 3-wire non-grounding
30A, 125/250V/AC
Non-NEMA



Receptacle Plug



3333RW

Plugs & connectors

Rating A	V/AC	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
30	125/250	Watertight	0.43-1.15" (10.9-29.2mm)	Y	□ 3331PW	□ 3333CW	•	•
		Watertight	0.43-1.15" (10.9-29.2mm)	BK	□ 3331PWBK	□ 3333CWBK	•	•
		Severe duty	0.38-1.00" (9.7-25.4mm)	Y & BK	□ 3331PY	□ 3333CY	•	

Receptacles

Rating A	V/AC	Description	Color	Single receptacle catalog no.		
30	125/250	Watertight	Y	□ 3333RW	•	•
		Watertight	BK	□ 3333RWBK	•	•

Complex environment locking devices

Product description

3-pole, 3-wire non-grounding
30A, 125/250V/AC
NEMA L10-30



L10-30R L10-30P

Plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.	
30	125/ 250	L10-30	Watertight	0.43-1.15" (10.9-29.2mm)	Y	□ L1030PW	□ L1030CW	•
			Watertight	0.43-1.15" (10.9-29.2mm)	BK	□ L1030PWBK	□ L1030CWBK	•
			Severe duty	0.38-1.00" (9.7-25.4mm)	Y & BK	□ L1030PY	□ L1030CY	•

Receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.	
30	125/ 250	L10-30	Watertight	Y	□ L1030RW	•
			Watertight	BK	□ L1030RWBK	•

Dimensional information:
D-34-35

Specification information:
Watertight industrial plugs & connectors: D-38
Watertight industrial receptacles: D-39
Severe duty industrial plugs & connectors: D-40

Color information:

BK (Black), Y (Yellow)



(Black)

(Yellow)

Compliances, specifications and availability are subject to change without notice.

 Indicates NAFTA compliant - Page Q-32

 RoHS compliant - Page Q-32