

Locking devices

Complex environment locking devices

Product description


4-pole, 4-wire non-grounding
20A, 3ØY 120/208V/AC
Non-NEMA



Receptacle Plug



L1820PW



L1820CW

3ØY plugs & connectors

Rating A	V/AC	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.	
20	120/208	3ØY watertight	0.43-1.15" (10.9-29.2mm)	Y	□ 7411PW	□ 7413CW	•
		3ØY watertight	0.43-1.15" (10.9-29.2mm)	BK	□ 7411PWBK	□ 7413CWBK	•
		3ØY severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	□ 7411PY	□ 7413CY	•


3ØY receptacles

Rating A	V/AC	Description	Color	Single receptacle catalog no.	
20	120/208	3ØY watertight	Y	□ 7413RW	•
		3ØY watertight	BK	□ 7413RWBK	•

Complex environment locking devices

Product description

4-pole, 4-wire non-grounding
20A, 3ØY 120/208V/AC
NEMA L18-20



L18-20R L18-20P

3ØY plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	120/208	L18-20	3ØY watertight	0.36-0.84" (9.1-21.3mm)	Y	□ L1820PW	□ L1820CW	•	•
			3ØY watertight	0.36-0.84" (9.1-21.3mm)	BK	□ L1820PWBK	□ L1820CWBK	•	•
			3ØY severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	□ L1820PY	□ L1820CY	•	•

3ØY receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.		
20	120/208	L18-20	3ØY watertight	Y	□ L1820RW	•	•
			3ØY watertight	BK	□ L1820RWBK	•	•

Dimensional information:
D-34-35

Specification information:
Watertight industrial plugs & connectors: D-38
Watertight industrial receptacles: D-39
Severe duty industrial plugs & connectors: D-40

Color information:

BK (Black), Y (Yellow)



Compliances, specifications and availability are subject to change without notice.

 Indicates NAFTA compliant - Page Q-32

 RoHS compliant - Page Q-32