

Complex environment locking devices

Product description

4-pole, 4-wire non-grounding
20A, 3ØY 277/480V/AC
NEMA L19-20




L19-20R **L19-20P**



L1920CW

3ØY plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	277/480	L19-20	3ØY watertight	0.36-0.84" (9.1-21.3mm)	Y	☐ L1920PW	☐ L1920CW	•	•
			3ØY watertight	0.36-0.84" (9.1-21.3mm)	BK	☐ L1920PWBK	☐ L1920CWBK	•	•
			3ØY severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	☐ L1920PY	☐ L1920CY	•	•



L1920RW


3ØY receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.		
20	277/480	L19-20	3ØY watertight	Y	☐ L1920RW	•	•
			3ØY watertight	BK	☐ L1920RWBK	•	•

Complex environment locking devices

Product description

4-pole, 4-wire non-grounding
20A, 3ØY 347/600V/AC
NEMA L20-20



L20-20R **L20-20P**

3ØY plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	347/600	L20-20	3ØY watertight	0.36-0.84" (9.1-21.3mm)	Y	☐ L2020PW	☐ L2020CW	•	•
			3ØY watertight	0.36-0.84" (9.1-21.3mm)	BK	☐ L2020PWBK	☐ L2020CWBK	•	•
			3ØY severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	☐ L2020PY	☐ L2020CY	•	•

3ØY receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.	
20	347/600	L20-20	3ØY watertight	Y	☐ L2020RW	•
			3ØY watertight	BK	☐ L2020RWBK	•

Dimensional information:
D-34-35

Specification information:
Watertight industrial plugs & connectors: D-38
Watertight industrial receptacles: D-39
Severe duty industrial plugs & connectors: D-40

Color information:
BK (Black), Y (Yellow)

BK (Black) Y (Yellow)

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32