

Complex environment locking devices

Product description

4-pole, 5-wire grounding
30A, 3ØY 277/480V/AC
NEMA L22-30



L22-30R L22-30P



L2330RW

3ØY plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
30	277/480	L22-30	3ØY severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	☐ L2230PY	☐ L2230CY	•	•
			3ØY watertight	0.43-1.15" (10.9-29.2mm)	Y	☐ L2230PW	☐ L2230CW	•	•
			3ØY watertight	0.43-1.15" (10.9-29.2mm)	BK	☐ L2230PWBK	☐ L2230CWBK	•	•


3ØY receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.		
30	277/480	L22-30	3ØY watertight	Y	☐ L2230RW	•	•
			3ØY watertight	BK	☐ L2230RWBK	•	•

Complex environment locking devices

Product description

4-pole, 5-wire grounding
30A, 3ØY 347/600V/AC
NEMA L23-30



L23-30R L23-30P

3ØY plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.	
30	347/600	L23-30	3ØY severe duty	0.63-1.16" (15.9-29.4mm)	Y & BK	☐ L2330PY	☐ L2330CY	•
			3ØY watertight	0.43-1.15" (10.9-29.2mm)	Y	☐ L2330PW	☐ L2330CW	•
			3ØY watertight	0.43-1.15" (10.9-29.2mm)	BK	☐ L2330PWBK	☐ L2330CWBK	•

3ØY receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.		
30	347/600	L23-30	3ØY watertight	Y	☐ L2330RW	•	•
			3ØY watertight	BK	☐ L2330RWBK	•	•

Dimensional information:
D-34-35

Specification information:
Watertight industrial plugs & connectors: D-38
Watertight industrial receptacles: D-39
Severe duty industrial plugs & connectors: D-40

Color information:
BK (Black), Y (Yellow)

BK (Black) Y (Yellow)

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32
RoHS compliant - Page Q-32