

## 30A Portable GFCIs

### Product description

2-pole, 3-wire grounding  
 30A, 120 V/AC; 30A, 208 V/AC  
 30A, 240 V/AC; 30A, 277 V/AC

### Features

- Housing is high-strength polycarbonate for durability
- Compact body design
- NEMA Type 4X<sup>†</sup> wet location rated for indoor/outdoor use
- Field wireable versions available for attachment to existing cords or equipment power supply
- Automatic and manual GFCI reset options available



GFI13M1NN



GFI13M144

### 30A inline series - field wireable, single phase



Rating A	Rating V/AC	NEMA Type†	Cord gauge	Plug type	Cord length	Catalog no.*
30	120	4X	10/3 AWG	Flying leads	2' (0.61m)	<input type="checkbox"/> GFI13M1NN
	240	4X	10/3 AWG	Flying leads	2' (0.61m)	<input type="checkbox"/> GFI23M1NN
	208	4X	10/3 AWG	Flying leads	2' (0.61m)	<input type="checkbox"/> GFI93M1NN
	277	4X	10/3 AWG	Flying leads	2' (0.61m)	<input type="checkbox"/> GFI23M1NN
120	4X	10/3 AWG	Flying leads	Flying leads	6' (1.83m)	<input type="checkbox"/> GFI13M2NN
	4X	10/3 AWG	Flying leads	Flying leads	6' (1.83m)	<input type="checkbox"/> GFI23M2NN
120	4X	10/3 AWG	Flying leads	Flying leads	25' (7.62m)	<input type="checkbox"/> GFI13M4NN
	4X	10/3 AWG	Flying leads	Flying leads	25' (7.62m)	<input type="checkbox"/> GFI23M4NN
120	4X	10/3 AWG	Flying leads	Flying leads	50' (15.24m)	<input type="checkbox"/> GFI13M6NN
	4X	10/3 AWG	Flying leads	Flying leads	50' (15.24m)	<input type="checkbox"/> GFI23M6NN
120	4X	10/3 AWG	Flying leads	Flying leads	100' (30.48m)	<input type="checkbox"/> GFI13M7NN
	4X	10/3 AWG	Flying leads	Flying leads	100' (30.48m)	<input type="checkbox"/> GFI23M7NN

†The housing and device must be 4X in order for the whole assembly to be 4X.

\*Automatic reset GFCIs also available. When ordering automatic portable GFCIs replace "M" in Catalog number with "A".  
 Example: GFI13A1NN = Automatic; GFI13M1NN = Manual.

### 30A inline series - molded locking plug & connector



Rating A	Rating V/AC	NEMA	Cord gauge	Plug type	Cord length	Catalog no.*
30	120	L5-30	10/3 AWG	Molded locking	2' (0.61m)	<input type="checkbox"/> GFI13M144
	240	L6-30	10/3 AWG	Molded locking	2' (0.61m)	<input type="checkbox"/> GFI23M144

\*Automatic reset GFCIs also available. When ordering automatic portable GFCIs replace "M" in Catalog number with "A".  
 Example: GFI13A144 = Automatic; GFI13M144 = Manual.

**Material characteristics:** Polycarbonate body. Temperature rating: -35°C to 66°C (-31°F to 151°F).  
**Compliances, specifications and availability are subject to change without notice.**