

Watertight portable GFCIs

Product description

2-pole, 3-wire grounding
15A, 120V/AC; 20A, 120V/AC; 20A, 240V/AC
30A, 120V/AC; 30A, 240V/AC

Features

- Housing is high-strength polycarbonate for durability
- Compact body design
- Field wireable versions available for attachment to existing cords or equipment power supply
- Automatic and manual GFCI reset options available



GFI12M155

15A, 20A and 30A inline series - watertight plug and connector



Rating A	V/AC	NEMA	NEMA Type	Cord gauge	Plug type	Cord length	Catalog no.*	
15	120	5-15	4X	12/3 AWG	Straight blade	2' (0.61m)	□ GFI11M155	•
					Straight blade	6' (1.83m)	□ GFI11M255	•
					Straight blade	25' (7.62m)	□ GFI11M455	•
					Straight blade	50' (15.24m)	□ GFI11M655	•
20	120	5-20	4X	12/3 AWG	Straight blade	2' (0.61m)	□ GFI12M155	
					Straight blade	6' (1.83m)	□ GFI12M255	
					Straight blade	25' (7.62m)	□ GFI12M455	
20	120	L5-20	4X	12/3 AWG	Locking	2' (0.61m)	□ GFI12M166	
					Locking	6' (1.83m)	□ GFI12M266	
					Locking	25' (7.62m)	□ GFI12M466	
20	240	L6-20	4X	12/3 AWG	Locking	2' (0.61m)	□ GFI22M166	
					Locking	6' (1.83m)	□ GFI22M266	
					Locking	25' (7.62m)	□ GFI22M466	
30	120	L5-30	4X	12/3 AWG	Locking	2' (0.61m)	□ GFI13M166	
					Locking	6' (1.83m)	□ GFI13M266	
					Locking	25' (7.62m)	□ GFI13M466	
30	240	L6-30	4X	12/3 AWG	Locking	2' (0.61m)	□ GFI23M166	
					Locking	6' (1.83m)	□ GFI23M266	
					Locking	25' (7.62m)	□ GFI23M466	

*Automatic reset GFCIs also available. When ordering automatic portable GFCIs replace "M" in Catalog number with "A".
Example: GFI11A155 = Automatic; GFI11M155 = Manual.

Material characteristics: Polycarbonate body. Temperature rating: -35°C to 66°C (-31°F to 151°F).
Compliances, specifications and availability are subject to change without notice.

RoHS compliant - Page Q-32