

Standard duty

Product description

Split lace
Single & double eye grips

Features & applications

- Split lace support grips are used when the end of the cable cannot easily be accessed and the support grip is intended for permanent installation
- Designed for loads up to 600 lbs. and vertical runs of no more than 100 ft.
- Wire mesh is produced from high quality, non-magnetic, tin coated bronze which provides superior corrosion resistance
- Support grips will hold more than one cable
- Absorbs additional strain from vibration, expansion, contraction and flexing
- Available in a variety of eye styles and cable ranges for supporting electrical and fiber optic cable, metal rods and tubing
- Single eye for use when cable is vertical and for applications where cable bends
- Double eye for use when cable is vertical and extends without bending



SGSL75



SGDL75

Single eye grips

Cord diameter	Bale length	Mesh length	Approx. break strength†	Catalog no.*	
0.50-0.61" (12.7-15.5mm)	7" (177.8mm)	11" (279.4mm)	770 lbs.	☐ SGSL50	•
0.62-0.74" (15.7-18.8mm)	8" (203.2mm)	11" (279.4mm)	960 lbs.	☐ SGSL63	•
0.75-0.99" (19.1-25.1mm)	8" (203.2mm)	14" (355.6mm)	1,320 lbs.	☐ SGSL75	•
1.00-1.24" (25.4-31.5mm)	9" (228.6mm)	15" (381.0mm)	1,680 lbs.	☐ SGSL100	•
1.25-1.49" (31.8-37.8mm)	10" (254.0mm)	16" (406.4mm)	1,680 lbs.	☐ SGSL125	•
1.50-1.74" (38.1-44.2mm)	12" (304.8mm)	18" (457.2mm)	1,680 lbs.	☐ SGSL150	•
1.75-1.99" (44.5-50.5mm)	14" (355.6mm)	20" (508.0mm)	2,640 lbs.	☐ SGSL175	•
2.00-2.49" (50.8-63.2mm)	16" (406.4mm)	22" (558.8mm)	3,760 lbs.	☐ SGSL200	•
2.50-2.99" (63.5-75.9mm)	18" (457.2mm)	24" (609.6mm)	3,760 lbs.	☐ SGSL250	•
3.00-3.49" (76.2-88.6mm)	21" (533.4mm)	26" (660.4mm)	5,040 lbs.	☐ SGSL300	•
3.50-3.99" (88.9-101.3mm)	24" (609.6mm)	28" (711.2mm)	5,040 lbs.	☐ SGSL350	•

Double eye grips

Cord diameter	Bale length	Mesh length	Approx. break strength†	Catalog no.*	
0.50-0.61" (12.7-15.7mm)	4" (101.6mm)	11" (279.4mm)	770 lbs.	☐ SGDL50	•
0.62-0.74" (15.7-18.8mm)	4" (101.6mm)	11" (279.4mm)	1,150 lbs.	☐ SGDL63	•
0.75-0.99" (19.1-25.1mm)	4" (101.6mm)	14" (355.6mm)	1,320 lbs.	☐ SGDL75	•
1.00-1.24" (25.4-31.5mm)	5" (127.0mm)	15" (381.0mm)	1,920 lbs.	☐ SGDL100	•
1.25-1.49" (31.8-37.9mm)	5" (127.0mm)	16" (406.4mm)	1,920 lbs.	☐ SGDL125	•
1.50-1.74" (38.1-44.2mm)	6" (152.4mm)	18" (457.2mm)	1,920 lbs.	☐ SGDL150	•
1.75-1.99" (44.5-50.5mm)	6" (152.4mm)	20" (508.0mm)	3,150 lbs.	☐ SGDL175	•
2.00-2.49" (50.8-63.2mm)	6" (152.4mm)	22" (558.8mm)	3,360 lbs.	☐ SGDL200	•
2.50-2.99" (63.5-75.9mm)	6" (152.4mm)	24" (609.6mm)	3,360 lbs.	☐ SGDL250	•
3.00-3.49" (76.2-88.6mm)	8" (203.2mm)	26" (660.4mm)	5,280 lbs.	☐ SGDL300	•
3.50-3.99" (88.9-101.3mm)	8" (203.2mm)	28" (711.2mm)	5,280 lbs.	☐ SGDL350	•

*Contact the factory for stainless steel support grips.

† To determine workload safety factor, divide approximate break strength by 10. See page N-34 for strength information. Consult factory for price and availability.

Compliances, specifications and availability are subject to change without notice.



Indicates NAFTA compliant - Page Q-30