

SCC Series Threaded Rigid Conduit and IMC Bolt-On™ Couplings

For Use with Threaded Rigid Conduit and IMC.

Applications

- Provides a fast inexpensive method of joining two sections of threaded rigid conduit in areas of close conduit spacing, tight clearance locations and irregular conduit bends which may normally require an expensive union.

Features

- Concretetight.
- Fast installation:
 - ① Slip Bolt-On™ Coupling over threaded end of one conduit section.
 - ② Butt the end of the second threaded conduit section to the first.
 - ③ Slip Bolt-On™ Coupling to the center of the two conduit threads and tighten bolt(s).

Material/Finish

- Coupling: malleable iron, zinc electroplated
- Hardware: steel, zinc electroplate
- Gasket: neoprene

Certifications and Compliances




- UL Standard: 514B
- UL Listed: E14814
- CSA Standard: C22.2 No. 18.4
- CSA Certified: 702992
- NEMA: FB-1




SCC-50



SCC-150

	Catalog Number	Trade Size (Inches)	Dimensions in Inches/Millimeters			Weight Lbs./Kgs. Per 100
			A	B	C	
	SCC-50	1/2	2.00/50.8	1.25/31.8	1.25/31.8	34.40/15.60
	SCC-75	3/4	2.31/58.7	1.25/31.8	1.50/38.1	39.40/17.87
	SCC-100	1	2.63/66.7	1.75/44.5	1.63/41.3	45.00/20.41
	SCC-125	1-1/4	2.63/66.8	2.13/54.0	1.63/41.3	60.00/27.22
	SCC-150	1-1/2	3.25/82.6	2.38/60.3	2.00/50.8	75.00/34.02
	SCC-200	2	3.50/88.9	2.75/69.9	2.06/52.4	108.00/48.99
	SCC-250	2-1/2	4.50/114.3	3.38/85.7	3.06/77.8	230.00/104.33
	SCC-300	3	5.00/127.0	4.00/101.6	3.38/85.7	300.00/136.08
	SCC-350	3-1/2	5.75/146.1	4.56/115.9	3.25/82.6	383.00/173.73
	SCC-400	4	6.25/158.8	5.13/130.2	3.38/85.7	415.00/188.24



COMMERCIAL PRODUCTS: RIGID AND IMC FITTINGS

Commercial Products