


# Intraground® N1 and N2 Series Control Stations

## Push Button and Push Button/Pilot Light. Nonmetallic

10 Ampere, 600 Vac Max. for Heavy Duty Use. N1 Series – Neutral Color; N2 Series – Blue Color.

**N1 Series (Non-Factory Sealed) ©**  
Class I, Division 1 and 2, Groups C, D  
NEMA 3R, 4X, 7CD, 12

**N2 Series (Factory Sealed)**  
Class I, Division 2, Groups B, C, D  
Class II, Division 1 and 2, Groups E, F, G  
Class III  
NEMA 3R, 4X, 9EFG, 12

		Hub Size (Inches)*	Description	Nameplate Marking	Catalog Number		
					N1 Series ©	N2 Series	
<b>1-Gang Push Buttons – Momentary Contact</b>							
 1 Circuit	 2 Circuit	<b>Dead-End</b>					
		1/2 or 3/4	1 Circuit Universal		Start/Stop	<b>N1D75-U1</b>	<b>N2D75-U1</b>
		1/2 or 3/4	2 Circuits Universal		Start/Stop	<b>N1D75-U2</b>	<b>N2D75-U2</b>
		<b>Feed-Thru</b>					
		1/2 or 3/4	1 Circuit Universal		Start/Stop	<b>N1DC75-U1</b>	<b>N2DC75-U1</b>
		1/2 or 3/4	2 Circuits Universal		Start/Stop	<b>N1DC75-U2</b>	<b>N2DC75-U2</b>
<b>1-Gang Push Buttons – Maintained Contact Red Mushroom Head – Emergency Stop Nameplate</b>							
		<b>Dead-End</b>					
	1/2 or 3/4	1 Circuit Universal		Emergency Stop	<b>N1D75-UM1</b>	<b>N2D75-UM1</b>	
		<b>Feed-Thru</b>					
1/2 or 3/4	1 Circuit Universal		Emergency Stop	<b>N1DC75-UM1</b>	<b>N2DC75-UM1</b>		
<b>3-Device Push Buttons – Momentary Contact</b>							
		<b>Dead-End</b>					
	1/2 or 3/4	3 Circuits Universal		Start/Stop	<b>N1D75-U3</b>	<b>N2D75-U3</b>	
		<b>Feed-Thru</b>					
1/2 or 3/4	3 Circuit Universal		Start/Stop	<b>N1DC75-U3</b>	<b>N2DC75-U3</b>		
<b>1-Gang Push Button/Pilot Light – Momentary Contact</b>							
 1 Circuit 1 Pilot Light	 2 Circuit 1 Pilot Lights	<b>Dead-End</b>					
		1/2 or 3/4	1 Circuit Universal and 1 Pilot Light		Specify	<b>N1D75-J1U1</b>	<b>N2D75-J1U1</b>
		1/2 or 3/4	2 Circuits Universal and 1 Pilot Light		Specify	<b>N1D75-J1U2</b>	<b>N2D75-J1U2</b>
		<b>Feed-Thru</b>					
		1/2 or 3/4	1 Circuit Universal and 1 Pilot Light		Specify	<b>N1DC75-J1U1</b>	<b>N2DC75-J1U1</b>
		1/2 or 3/4	2 Circuits Universal and 1 Pilot Light		Specify	<b>N1DC75-J1U2</b>	<b>N2DC75-J1U2</b>
<b>1-Gang Pilot Lights</b>							
 1 Pilot Light	 2 Pilot Lights	<b>Dead-End</b>					
		1/2 or 3/4	1 Pilot Light		Specify	<b>N1D75-J1</b>	<b>N2D75-J1</b>
		1/2 or 3/4	2 Pilot Lights		Specify	<b>N1D75-J2</b>	<b>N2D75-J2</b>
		<b>Feed-Thru</b>					
1/2 or 3/4	1 Pilot Light		Specify	<b>N1DC75-J1</b>	<b>N2DC75-J1</b>		
1/2 or 3/4	2 Pilot Lights		Specify	<b>N1DC75-J2</b>	<b>N2DC75-J2</b>		

\* Furnished with 3/4" to 1/2" NPT reducer.

© For Class I, Division 1 applications, sealing fittings must be field installed adjacent to enclosure on all conduit runs.