



FM9™ Aluminum Unilet® Covers, Gaskets and Wiring Capacity

For use with Rigid Steel, Rigid Aluminum and IMC Conduit.

FITTINGS: CONDUIT BODIES

Appleton FM9 Blank Covers and Gaskets and Stamped Aluminum Cover with Integral Gasket

(Covers furnished with Stainless Steel Screws)

Body Size (Inches)	Stamped Aluminum Cover ‡	Solid Gasket Neoprene
		
1/2	190	GASK1941
3/4	290	GASK1942
1	390	GASK1943
1-1/4	490	GASK1944
1-1/2	590	GASK1945
2	690	GASK1946
2-1/2	889	GASK808N
3	889	GASK808N
3-1/2	989	GASK809N
4	989	GASK809N

Wiring Capacity: Combine Body and Cover Capacities for Total usable Capacity per NEC 314.16(A)

Hub Size (Inches)	Capacity (in ³ /dm ³)						Cover
	C	LB	LL LR	T	TB	X	
1/2	4.80/0.08	5.00/0.08	5.30/0.09	5.00/0.08	6.80/0.11	7.30/0.12	0.50/0.01
3/4	7.80/0.13	8.30/0.14	8.50/0.14	8.30/0.14	11.00/0.18	11.30/0.19	0.80/0.01
1	12.30/0.20	12.80/0.21	13.30/0.22	12.50/0.20	16.50/0.27	17.00/0.28	1.00/0.02
1-1/4	25.30/0.41	26.50/0.43	27.30/0.45	26.30/0.43	25.80/0.42	–	1.50/0.02
1-1/2	37.50/0.61	39.00/0.64	39.80/0.65	38.50/0.63	38.50/0.63	–	2.50/0.04
2	77.50/1.27	81.30/1.33	82.80/1.36	79.50/1.30	77.00/1.26	–	6.50/0.11
2-1/2	230.00/3.77	230.00/3.77	230.00/3.77	230.00/3.77	–	–	12.30/0.20
3	250.00/4.10	250.00/4.10	250.00/4.10	250.00/4.10	–	–	12.30/0.20
3-1/2	450.00/7.37	450.00/7.37	450.00/7.37	450.00/7.37	–	–	24.00/0.39
4	470.00/7.70	470.00/7.70	470.00/7.70	470.00/7.70	–	–	24.00/0.39

‡ PVC coating available on select FM9 covers. Add suffix **-PVC** to catalog number.