

## ULTRA™ Series Fan and Fan/Light Features

- HVI certified at <0.3 Sones, ULTRA Silent™ Sound Technology provides the quietest sound rating obtainable
- 50, 80 or 110 CFM
- Intermittent and continuous ventilation
- ULTRA Smart™ Control Technology monitors performance and adjusts motor speed to ensure rated air movement
- ENERGY STAR® qualified with ULTRA Green™ DC Motor Technology
- ULTRA Quick™ Installation Technology saves time with the fastest, easiest, most universal installation
- XN and ZN models feature 6" ducting—50 and 80 CFM models include an optional 6" to 4" duct reducer
- Bright, energy efficient 36-watt fluorescent lighting
- UL Listed for use over bathtub or shower when connected to a GFCI protected branch circuit
- Type IC
- Fits 2" x 8" ceiling construction
- Optional RDFI Premium Radiation Damper Kit available for models ZN110, ZN80, XN110, XN80 & XN50

Model	CFM	Sones	Light <sup>1</sup> / Night Light	Humidity Sensing	Motion Sensing	ENERGY STAR®	Ducting
<b>Single-speed Fans</b>							
XN50	50	<0.3	—	—	—	Yes	6"
	50	<0.3	—	—	—	Yes	6" to 4" reducer
XN80	80	<0.3	—	—	—	Yes	6"
	80	0.3	—	—	—	Yes	6" to 4" reducer
XN110	110	<0.3	—	—	—	Yes	6"
XN110H	110	<0.3	—	Yes	—	Yes	6"
<b>Single-speed Fan/Lights</b>							
XN50L	50	<0.3	2-18W GU24 / 4W	—	—	Yes	6"
	50	<0.3	2-18W GU24 / 4W	—	—	Yes	6" to 4" reducer
XN80L	80	<0.3	2-18W GU24 / 4W	—	—	Yes	6"
	80	0.3	2-18W GU24 / 4W	—	—	Yes	6" to 4" reducer
XN110L	110	<0.3	2-18W GU24 / 4W	—	—	Yes	6"
XN110HL	110	<0.3	2-18W GU24 / 4W	Yes	—	Yes	6"
<b>Multi-speed Fans</b>							
ZN80	80	<0.3	—	—	—	Yes	6"
	80	0.3	—	—	—	Yes	6" to 4" reducer
ZN80M	80	<0.3	—	—	Yes	Yes	6"
	80	0.3	—	—	Yes	Yes	6" to 4" reducer
ZN110	110	<0.3	—	—	—	Yes	6"
ZN110H	110	<0.3	—	Yes	—	Yes	6"
ZN110M	110	<0.3	—	—	Yes	Yes	6"
<b>Multi-speed Fan/Lights</b>							
ZN80L	80	<0.3	2-18W GU24 / 4W	—	—	Yes	6"
	80	0.3	2-18W GU24 / 4W	—	—	Yes	6" to 4" reducer
ZN80ML	80	<0.3	2-18W GU24 / 4W	—	Yes	Yes	6"
	80	0.3	2-18W GU24 / 4W	—	Yes	Yes	6" to 4" reducer
ZN110L	110	<0.3	2-18W GU24 / 4W	—	—	Yes	6"
ZN110HL	110	<0.3	2-18W GU24 / 4W	Yes	—	Yes	6"
ZN110ML	110	<0.3	2-18W GU24 / 4W	—	Yes	Yes	6"



ENERGY STAR® fans use 65% less energy, on average, than standard models and may qualify for local utility rebates. ▲ See page 45 for 6" ducting (DT6W) product specifications.



<sup>1</sup>Bulb included

### RDFI Premium Radiation Damper

When the air temperature passing through the damper exceeds 165°F the fusible link melts, triggering the thermal fabric to automatically close across the damper. Airflow is interrupted by a flame and heat barrier, preventing the rapid spread of fire to other areas.

- Galvanized steel frame
- High temperature, non-asbestos, reinforced fiber thermal fabric
- Stainless steel closure springs
- 165°F fusible link
- Use the same grille provided with the ULTRA™ Series fan



Also works with LoProfile fan LPN80.