

Clamp On Service Entrance Heads



Use:

Service entrance caps are used as a connecting point in an overhead service entrance and can be mounted on threaded or unthreaded Rigid Conduit, IMC or EMT Conduit.

- Clamp-On Type
- Phenolic Insulator with Multiple Holes
- Listed for Use in Wet Locations

Materials

- Aluminum Die-Cast

Certification



Standards

UL 514B CSA C22.2 No. 18
NEC Articles 345, 346 & 348

Threaded Service Entrance Heads



Use:

Service entrance caps are used as a connecting point in an overhead service entrance and can be mounted on threaded Rigid Conduit and IMC.

- Threaded Type
- Phenolic Insulator with Multiple Holes
- Listed for Use in Wet Locations

Materials

- Aluminum Die-Cast

Certification



Standards

UL 514B CSA C22.2 No. 18
NEC Articles 345, 346 & 348

NM / SE CABLE

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			
Boxed								
180	70905-9	1/2"	2.25	2.22	1.93	-	50	24
181	70910-3	3/4"	2.48	2.51	2.20	-	50	24
182	70915-8	1"	2.75	2.85	2.55	-	25	10
183	70920-2	1 1/4"	3.12	2.90	2.98	-	25	14
184	70925-7	1 1/2"	3.75	3.68	3.18	-	15	13
185	70930-1	2"	4.34	5.28	4.61	-	5	8
1866	70935-6	2 1/2"	5.64	5.52	5.20	-	1	4.5
2877	70932-5	3"	6.39	6.25	5.26	-	1	7
2888	70945-5	3 1/2"	6.82	6.85	7.16	-	1	6.5
2899	70950-9	4"	7.65	6.85	7.25	-	1	6.5

NM / SE CABLE

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			
Boxed								
8160	08160-5	1/2"	0.97	2.19	2.04	-	5/50	15
8161	08161-2	3/4"	1.16	2.41	2.13	-	5/25	8.8
8162	08162-9	1"	1.51	2.83	2.54	-	10	4.8
8163	08163-6	1 1/4"	1.89	2.89	3.00	-	10	5.2
8164	08164-3	1 1/2"	2.16	3.51	3.20	-	10	5.2
8165	08165-0	2"	2.70	4.36	4.58	-	5	7.7