


Plastic Insulating Bushings



Use:

Plastic insulating bushings are used on the end of Rigid and IMC Conduits and other threaded connectors to provide a smooth well rounded bearing surface to protect wires or cables.

- Rated 105°C
- Flame Retardant

Materials

- Thermoplastic

Finish

- Grey

Certification

UL E121487


Standards

UL 514B CSA C22.2 No. 18 NEMA FB-1

RIGID CONDUIT

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Ctn/Case Qty/Qty	Case Wt.
			A	B	C		
Boxed							
171	09003-3	1/2"	1.04	0.39	0.60	100/1000	7.4
172	70710-9	3/4"	1.27	0.41	0.78	100/1000	9.7
173	70715-4	1"	1.55	0.56	1.00	50/500	9.6
174	70720-8	1 1/4"	1.90	0.57	1.33	25/250	7.4
175	70725-3	1 1/2"	2.18	0.57	1.54	50	1.9
176	70730-7	2"	3.17	0.73	2.36	50	2.3
177	70735-2	2 1/2"	3.17	0.73	2.36	25	2.0
178	70740-6	3"	3.80	0.76	3.00	25	2.4
179	70745-1	3 1/2"	3.80	0.76	3.00	25	2.4
170	70750-5	4"	3.80	0.76	3.00	25	2.4

Insulated Metallic Grounding Bushings w/ Lay-In Lug



Use:

Insulated metallic grounding bushings are used on the end of Rigid and IMC Conduits and other threaded connectors to provide a smooth well rounded bearing surface to protect wires or cables as well as providing a means to connect a grounding conductor.

- Nylon Liner Rated 150°C
- 90°C Dual Rated Lay-in Aluminum Lug

Materials

- Zinc Die-Cast

Certification

UL E88878 SSB LR57925

Standards

UL 467 CSA C22.2 No. 41
NEMA FB-1 NEC Article 345 & 346

RIGID CONDUIT

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			
Boxed								
8270	08270-1	1/2"	1.04	0.50	0.54	-	100/500	16.2
8271	08271-8	3/4"	1.28	0.50	0.74	-	50/250	21.5
8272	08272-5	1"	1.52	0.59	0.96	-	50/250	27.2
8273	08273-2	1 1/4"	1.87	0.61	1.27	-	25/125	13.5
8274	08274-9	1 1/2"	2.16	0.60	1.49	-	25/125	17.9
8275	08275-6	2"	2.67	0.60	1.95	-	10/50	22.9
8276	08276-3	2 1/2"	1.52	0.59	0.96	-	10	27.2
8277	08277-0	3"	1.87	0.61	1.27	-	5/25	13.5
8278	08278-7	3 1/2"	2.16	0.60	1.49	-	10	17.9
8279	08279-4	4"	2.67	0.60	1.95	-	10	22.9