



Ebinger Manufacturing Co
"The Race for Quality and Value Has No Finish Line"

Description: DROP-IN ANCHORS



Can be used in cinder block or concrete.

Ideal for hanging pipe, duct work, machinery. UL Listed sizes include 3/8" to 3/4" diameter.

MATERIAL: Carbon

Finish: Zinc Plated

Status: Active

NAED#	Part#	ANCHOR DIAMETER	DRILL BIT DIAMETER	MIN. EMBEDMENT	REQUIRED TORQUE	2000 PSI CONCRETE TENSION (LBS)	4000 PSI CONCRETE TENSION (LBS)	Barcode#	Package QTY	Weight
02990	DA1/4	1/4"	3/8"	1"	5	939	2,067	718205029909	100	2.5 LBS
02991	DA3/8	3/8"	1/2"	1-9/16"	10	1,560	3,995	718205029916	100	6.25 LBS
02992	DA1/2	1/2"	5/8"	2"	20	3,105	4,110	718205029923	50	6 LBS
02993	DA5/8	5/8"	7/8"	2-1/2"	40	3,323	5,750	718205029930	25	4.88 LBS
02994	DA3/4	3/4"	1"	3-1/8"	80	6,678	10,807	718205029947	25	12.50 LBS

For further technical information, please contact us.

Ebinger Manufacturing Co
7869 Kensington Ct.
Brighton, MI 48116

Hours: 8AM-5PM EST
Monday-Friday
Phone (248)486-8880
Fax (248)486-8080
emc48116@hotmail.com