



A.



B.



C.



D.



E.

Plastic In-Use Covers Single-Gang



- Complies with 2011 NEC Article 406.9 (B1)
- Heavy-duty polycarbonate construction
- Vertical/horizontal hinge configuration
- Pre-adhered gasket
- Meets requirements for Cold Impact Testing at -60°F (-51°C)
- Packaged with 3 patented inserts for GFCI, duplex, toggle, or round receptacles
- Limited 1-year warranty

Model #	Flexi-Guard Inserts	Cord Diam.	Max. Cord Gauge	Depth	Color	Lockable Hasp Diam.
A. WP3100C*	WP17	0.5"	(2) 14 or (1) 12 Gauge	2 3/4"	Clear	For .125" lock
B. WP3103C**	WP17	0.5"	(2) 14 or (1) 12 Gauge	2 3/4"	Clear	For .125" lock
C. WP1100C	WP17	0.5"	(2) 14 or (1) 12 Gauge	2 3/4"	Clear	For .250" lock
D. WP1100WC	WP17	0.5"	(2) 14 or (1) 12 Gauge	2 3/4"	White	For .250" lock
WP1110C	WP17	0.5"	(2) 14 or (1) 12 Gauge	3 5/8"	Clear	For .250" lock
E. WP1110GC	WP17	0.5"	(2) 14 or (1) 12 Gauge	3 5/8"	Gray	For .250" lock
WP1110WC	WP17	0.5"	(2) 14 or (1) 12 Gauge	3 5/8"	White	For .250" lock

*Hidden hinge

**Includes 3/0 Adapter Plate for 3" Round Box