

PS3000

Pool and Spa Surge Protective Device



- Meets ANSI UL1449 3rd Edition Standards
 - 120/240 VAC single split phase SPD for use on a variety of pool equipment
 - Green LED Protection Indicator
 - Type 4x enclosure
 - ½" x 20 threaded nipple (weatherproof and UV resistant)
 - TPMOV® Technology
 - 3 modes of protection
 - 3 leads
 - 18" lead length
 - 10 gauge leads
 - 3-year warranty
 - \$7,500 connected equipment warranty



Model #	Service Voltage	SPD Type	Nominal Discharge Current	MCOV*		Wiring Configuration	SCCR**	Voltage Protection Rating (VPR)		
				L-N	L-L			L-N/G	N-G	L-L
PS3000	120/240 VAC	1 or 2	10kA	150V	300V	L1, L2, L/N-G	20kA	600	900	

*MCOV Maximum Continuous Operating Voltage

**SCCB Short Circuit Current Rating

IG1200RC3

Plastic Housing



- Green LED Protection Indicator
 - Type 3R rainproof enclosure
 - 5.65" (14.35 cm) H x 4.18" (10.62 cm) W x 3.33" (8.46 cm) D
 - 3 modes of surge protection (L1-N,L2-N,L1-L2)
 - 3 leads
 - 30" lead length
 - 3-year warranty
 - \$7,500 connected equipment warranty



Model #	Service Voltage	Type	Wiring Configuration	Nominal Discharge Current	MCOV*	SCCR**	Voltage Protection Rating (VPR)				
							L-N/G	L-N	L-G	N-G	L-L
IG1200RC3	120, 240 VAC	1 or 2	L1, L2, N/GND	20 kA	150 L-N, N-G 300 L-L, L-G	50 kA	700			1200	

*MCOV Maximum Continuous Operating Voltage

****SCCR Short Circuit Current Rating**