



T100 Series 24-Hour Time Switches



- Direct 24-Hour control of most loads
- Up to 12 ON/OFF operations each day with minimum ON/OFF times of one hour
- Manual override
- One ON and one OFF tripper included

A. Mechanism Only

Model #	Switch	Input Voltage	HP Rating
T101M	SPST	125 VAC, 60Hz	2
T103M	DPST	125 VAC, 60Hz	2
T104M	DPST	208-277 VAC, 60Hz	5
T106M **	1NO/1NC	208-277 VAC, 60Hz	5

B. Steel Indoor Enclosure

Model #	Switch	Input Voltage	HP Rating
T101	SPST	125 VAC, 60Hz	2
T102	SPST	208-277 VAC, 60Hz	5
T103	DPST	125 VAC, 60Hz	2
T104	DPST	208-277 VAC, 60Hz	5
T104-50	DPST	208-277 VAC, 50Hz	5
T101B*	SPST	125 VAC, 60Hz	2
T105 **	1NO/1NC	125 VAC, 60Hz	2

C. Steel Indoor/Outdoor Enclosure

Model #	Switch	Input Voltage	HP Rating
T101R	SPST	125 VAC, 60Hz	2
T102R	SPST	208-277 VAC, 60Hz	5
T103R	DPST	125 VAC, 60Hz	2
T104R	DPST	208-277 VAC, 60Hz	5
T106R**	1NO/1NC	208-277 VAC, 60Hz	5

D. Plastic Indoor/Outdoor Enclosure

Model #	Switch	Input Voltage	HP Rating
T101P	SPST	125 VAC, 60Hz	2
T102P	SPST	208-277 VAC, 60Hz	5
T103P	DPST	125 VAC, 60Hz	2
T104P	DPST	208-277 VAC, 60Hz	5

E. See-Through Indoor/Outdoor Enclosure

Model #	Switch	Input Voltage	HP Rating
T101PCD82	SPST	125 VAC, 60Hz	2
T103PCD82	DPST	125 VAC, 60Hz	2
T104PCD82	DPST	208-277 VAC, 60Hz	5

*Separate clock motor terminals for switching circuits not on line voltage.
**Can be wired as SPDT

Ratings:
Switch Ratings: 40 A Resistive each pole, 120-480 VAC, 40 A Inductive Tungsten, 120, 240 or 277 VAC, 1000 VA Pilot Duty each pole, 120-277 VAC, 2 HP, (24 FLA), 120 VAC, 5 HP, (28 FLA), 240 VAC

Power Consumption: 3 W max.
Operating Temperature: -40°F to 130°F (-40°C to 54°C)
Warranty: 1 year

For optional enclosure, see page 146; For additional trippers, see page 153; For replacement motors, see page 153

