



FWZ53 Series AC Hour Meters



- Non resettable
- Optional gasket to achieve IP54 rating
- White numerals on black background with tenths/hundredths numerals in yellow

	Model #	Input Voltage	Frequency
A.	FWZ53-120/50U	120 VAC	50 Hz
	FWZ53-120U	120 VAC	60 Hz
	FWZ53-220/50U	220 VAC	50 Hz
	FWZ53-24U	24 VAC	60 Hz

Ratings:

Bezel: 2.09" x 1.02" (53 mm x 26 mm)
Capacity: 99,999.99 hours
Digits: 0.16" high numerals
Power Consumption: 1 VA
Operating Temperature: -40°F to 160°F (-40°C to 72°C)
Termination: Combination ¼" spade and screw clamp
Mounting: Flush-panel retainer mounted (2) 0.150" holes for #6 screws
Panel Opening: 1.50" x 1.00" rectangular (38 x 25 mm)



FWZ55 Series AC Hour Meters



- Non resettable
- Optional gasket to achieve IP54 rating
- White numerals on black background with tenths/hundredths numerals in yellow

	Model #	Input Voltage	Frequency
B.	FWZ55-120U	120 VAC	60 Hz
	FWZ55-220/50	220 VAC	50 Hz
	FWZ55K-120U	120 VAC	60 Hz
	FWZ55K-220/50	220 VAC	50 Hz
	FWZ55K-240U	240 VAC	60 Hz

Ratings:

Bezel: 2.36" x 1.36" (60 mm x 34.5 mm)
Capacity: 99,999.99 hours
Digits: 0.16" high numerals
Operating Temperature: -40°F to 160°F (-40°C to 72°C)
Power Consumption: 1 VA
Termination: Combination ¼" spade and screw clamp. Rear access screw terminals available (models with "K" suffix)
Mounting: Flush-panel retainer mounted with slip-on plastic retaining bracket
Panel Opening: 2.06" x 1.08" rectangular (52 mm x 27.5 mm)

FWZ53 & FWZ55 Series Gasket

Model #	Description
G-55U	Gasket for FWZ53 & FWZ55
G-53U	Gasket for FWZ53