Rugged and Tough

Hour Meters built to withstand up to an environmental rating of IP54



FWZ72 Series AC Hour Meters









- Non resettable
- Optional gasket to achieve IP54 rating
- White numerals on black background with tenths and hundredths numerals in yellow

	Model #	Input Voltage	Frequency	Color
C.	FWZ72-120U	120 VAC	60 Hz	Black
	FWZ72-24U	24 VAC	60 Hz	Black
D.	FWZ72B-120U	120 VAC	60 Hz	Blue, Silver, Clear
	FWZ72B-240U	240 VAC	60 Hz	Blue, Silver, Clear
E.	FWZ72C-120	120 VAC	60 Hz	Clear Frosted
	FWZ72K-240U	240 VAC	60 Hz	Black



Bezel: 2.83" round (72 mm), 3 hole Capacity: 99,999.99 hours

Digits: 0.16" high numerals Power Consumption: 1VA

Operating Temperature: -40°F to 160°F (-40°C to 72°C) Termination: Combination 1/4" spade and screw clamp Rear access screw terminals available (models with "K" suffix)

Mounting: Flush-panel mounted with three 0.185" holes for #8 screws Panel Opening: 1.75" round (44.5 mm) or 1.50"x 1" rectangular

(38 mm x 24 mm)





FWZ72 Series Gasket

Model #	Description
G-72U	Gasket for FWZ72