

Timer Controls: DIN Rail Time Switches

talento smart B25 | 43.02.0002.1



# DISCOVER MORE

### talento smart B25

### 43.02.0002.1

Highlights among the digital DIN rail time switches are the talento smart series models. Developed specifically for the requirements of installers, they are equipped with a variety of technological innovations such as the WILDCARD function for simple programming of recurring events or the QUICK COPY function for a quick transfer of existing programs. A special feature of talento smart: All time switches can also be easily and quickly programmed on the PC or smart phone and transmitted via the integrated Bluetooth interface on the time switch.

Bluetooth® connectivity and mobile programming tools make the talento smart Series a perfect choice for a variety of time switch tasks. Its compact, DIN rail mountable design allows for quick installation into existing infrastructures, while Bluetooth integration makes it easy to program the time switch without opening the control cabinet. Boost productivity by updating schedules from a smartphone or tablet using the complimentary talento

Read More 🗸













## Features & Applications

## **Features**

- Wireless Bluetooth 4.0 Connectivity
- Zero-Crossing Technology
- Mobile Programming via the talento smart App
- · Easy and fast installation
- Optimal tamper protection through PIN code protection
- Optimal tamper protection through sealable housing
- Auto Daylight Saving Time feature
- · 365-Day Scheduling
- Up to 500 Events (on "C" models only)
- Astronomic Control (on "C" models only)

# **Applications**

- · Hydroponic Systems
- · Sports Fields
- Ponds
- · Parking Lots
- Retail Stores
- Fountains
- · Outdoor Signage
- Indoor Lighting

### **Specifications**

Mechanism Type

Digital/Electrical

Maximum Power Consumption (VA)

C

Switch Type

**SPDT** 

Operating Temperature Max (F)
131

Operating Temperature Min (°C)

-20

Cut-Out Width (mm)

0

Shipping Weight (kg)

0

Shipping Weight (lbs)

0

Operating Temperature Max (°C) <sup>55</sup>	Operating Temperature Min (F) -4	Warranty 1-year
	Cut-Out Height (mm)	

Videos

Copyright © 2017 Intermatic Incorporated. All rights reserved.