



PART NUMBER: 966956
DESCRIPTION: 24 AWG /4 Pair Category 5e CMP
COMPLIANCE:

- ETL Listed Type CMP
- C(ETL) listed CMP FT6
- ETL Verified to ANSI/TIA 568-C.2
- Tested to 350 MHz

Construction Parameters:

Conductor	24 AWG Solid Bare Copper	<u>DIAMETER*</u>
Dielectric	Solid FEP	0.020"
Assembly	Each pair has different lay length for cross-talk prevention and ripcord added.	0.035"
Jacket	PVC	0.185"

* = Nominal value

Product Electrical Characteristics:

Max Capacitance (nF/100m @ 1 kHz)	Max DC Resistance (Ω/100m @ 20°C)	Max Delay Skew (ns/100m)	Nom Velocity of Propagation (%)	Characteristic Impedance (Ω @ 1-100 MHz)
5.6	9.38	45	68	100 +/- 15

Freq (MHz)	Max Insertion Loss (dB/100m)	Min NEXT Loss (dB)	Min PSNEXT Loss (dB)	Min ACR (dB/100m)	Min PSACR (dB/100m)	Min ACRF (dB/100m)	Min PSACRF (dB/100m)	Min Return Loss (dB)
1	2.0	65.3	62.3	63.3	60.3	63.8	60.8	20
10	6.5	50.3	47.3	43.8	40.8	43.8	40.8	25
16	8.2	47.3	44.3	39.1	36.1	39.7	36.7	25
20	9.3	45.8	42.8	36.5	33.5	37.7	34.7	25
31.25	11.7	42.9	39.9	31.2	28.2	33.9	30.9	23.6
62.5	17.0	38.4	35.4	21.4	18.4	27.8	24.8	21.5
100	22.0	35.3	32.3	13.3	10.3	23.8	20.8	20.1
155	28.1	32.4	29.4	4.3	1.3	20.0	17.0	18.8
200	32.4	30.8	27.8	-	-	17.8	14.8	18.0
250	36.9	29.3	26.3	-	-	15.8	12.8	17.3
350	44.9	27.1	24.1	-	-	12.9	9.9	16.3

** Note that values above 100 MHz are not guaranteed and are for engineering reference only.*

Pair Colors: W/BL with BL, W/OR with O, W/GR with GR, W/BR with BR
Jacket Color: Standard colors are White, Yellow, Orange, Green, Blue, Gray and Black

Legend (Ink Print) CAT5E COLEMAN CABLE 966956 CAT5E 24 AWG 4PR UTP C(ETL)US LISTED (ETL CODE) TYPE CMP FT6 TESTED TO 350 MHZ ETL VERIFIED TO ANSI/TIA-568-C.2 CAT 5E
(Also printed with sequential footage & date code)

Temperature Rating: -10^o C TO 60^o C

This product complies with European Directive 2011/65/EU (RoHS-2)
On special orders, the customer will accept all mil lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire. Any information contained herein shall not be disclosed to any party without written consent of Southwire.

Specification Issue Date: March 3, 2015