

Fluorescent Utility Lights

Applications

- Whether the application calls for securely lighting a livestock operation, damp barn, or even a harsh, outdoor environment, the 22 Watt fluorescent utility light delivers energy-efficient, trouble-free service for a variety of demanding lighting needs. The single unit incorporates non-corrosive construction, its own wiring compartment, and an impact-resistant thermoplastic mounting base.

Features

- Removable globe for effortless “push-pull” relamping and cleaning.
- Standard 0.59"/15 mm, 22 Watt quad-tube lamp provides 75% greater energy efficiency.
- Average service life of 10,000 hours.
- Fastens directly to walls, ceilings, or structural members.
- 3-1/2"/88.9 mm diameter, 9-1/2"/241.3 mm height.
- Two 5/16"/7.9 mm diameter mounting holes on 4-3/8"/111.3 mm centers.
- 22 Watt, 120 Volt PLC, 0.59"/15 mm lamp equivalent to 75 Watt incandescent.
- Delivered complete with globe, ballast, lamp, socket and wiring box.
- For use up to 100 °F/38 °C ambient temperature.
- Use with either 1/2"/12.7 mm or 3/4"/19.1 mm rigid non-metallic conduit.



600-FL22

Options

- CSA Certified versions available. Items available in a CSA version will be marked with a **C**. Add the prefix **C** to the beginning of the catalog number.

Certifications and Compliances

- UL Listed: E13761
- UL Standard: 1598
- CSA Certified: LL56247
- CSA Listed: C22.2 No. 250.0

	Wiring Compartment Cubic Inch/Cubic Decimeter	Supply Wire Rating °F/°C	Catalog Numbers	
			1/2"/12.7 mm Threaded Conduit Opening	3/4"/19.1 mm Threaded Conduit Opening
Utility light with glass globe				
For damp locations	12/0.20	194/90	600-FL22	601-FL22
For damp locations	12/0.20	221/105	C600-FL22 [†]	C601-FL22 [†]
Sealed unit for wet locations	12/0.20	194/90	605-FL22	606-FL22
Sealed unit for wet locations	12/0.20	221/105	C605-FL22 [†]	C606-FL22 [†]
Utility light with clear plastic prismatic globe				
For damp locations	12/0.20	194/90	640-FL22	641-FL22
For damp locations	12/0.20	221/105	C640-FL22 [†]	C641-FL22 [†]
Sealed unit for wet locations [ⓘ]	12/0.20	194/90	645-FL22	646-FL22
Sealed unit for wet locations [ⓘ]	12/0.20	221/105	C645-FL22 [†]	C646-FL22 [†]
Utility light with red plastic prismatic globe				
For damp locations	12/0.20	194/90	650-FL22	651-FL22
For damp locations	12/0.20	221/105	C650-FL22 [†]	C651-FL22 [†]
Sealed unit for wet locations [ⓘ]	12/0.20	194/90	655-FL22	656-FL22
Sealed unit for wet locations [ⓘ]	12/0.20	221/105	C655-FL22 [†]	C656-FL22 [†]

Accessories and Replacement Parts — Additional plastic globes see Protect-O-Globes

	Catalog Number
Glass globe only - 6-11/16"/220.7 mm long	0753
Clear plastic prismatic globe only - 8-1/4"/209.6 mm long	5213-6649
Red plastic prismatic globe only - 8-1/4"/209.6 mm long	5213-6659
Protective metal cage for glass globes only	1435-6
22 Watt, 120 Volt PLC, 0.59" /15 mm lamp	5213-6660
Base, socket, and ballast assembly only for 600-FL22	5213-6623
Base, socket, ballast, and seal assembly only for 605-FL22	5213-6625

[ⓘ] For base-up operation only.

[†] CSA Certification only.