


Metallics

An **AMERICAN** Source For Premier
and Innovative Fasteners and Anchors

BUTTON HEAD HEX PIN TAMPER-RESIST SHEET METAL SCREW – 18-8 STAINLESS STEEL

The following Specification Sheet applies to all **Button Head Hex Pin Tamper-Resist Machine Screw – 18-8 Stainless Steel** in our **TP5** series.



Size	A		H		S	J	T	F		B
	Head Diameter		Head Height		Head Side Height	Hexagon Socket Size	Key Engagement	Fillet Transition Diameter		Pin Diameter
	Max.	Min.	Max.	Min.	Ref.	Nom	Min.	Max.	Min.	Ref.
8	.312	.298	.087	.077	.015	1/8	.052	.194	.184	.048
10	.361	.347	.101	.091	.020	5/32	.070	.220	.210	.062
14	.437	.419	.132	.122	.031	5/32	.087	.290	.280	.062

*The maximum post height must be flush with the top of the head. The minimum post height must be controlled so the top of the post will not be below flush surface of the head by more than the fall away gage penetration.


Metallics

229 Cross Street
Bristol, CT 06010

www.metallics.us

Phone: 860 589-4186 Toll Free: 800 243-8272


Fax: 860 584-1008 Toll Free Fax: 800 831-9358



Metallics

An **AMERICAN** Source For Premier
and Innovative Fasteners and Anchors

THREAD DIMENSIONS



THREADS FOR SELF-TAPPING SCREWS TYPE AB							ASME B18.6.3-2013		
Nominal Size or Basic Screw Diameter		Threads Per Inch	D		d		L		Minimum Torsional Strength, lb.- in. (STEEL SCREWS ONLY)
			Major Diameter		Minor Diameter		Minimum Practical Screw Length		
			Max	Min	Max	Min	90° Heads	Csk Heads	
6	.1380	20	.139	.132	.104	.099	9/32	11/32	24
7	.1510	19	.154	.147	.115	.109	5/16	3/8	30
8	.1640	18	.166	.159	.122	.116	5/16	3/8	39
10	.1900	16	.189	.182	.141	.135	3/8	7/16	56
12	.2160	14	.215	.208	.164	.157	7/16	21/32	88
1/4	.2500	14	.246	.237	.192	.185	1/2	19/32	142
Tolerance on Length				Up to 1" Incl.: ±0.03			Over 1": ±0.05		

Description	A thread forming tapping screw with spaced threads and a gimlet point.
Applications/ Advantages	For self starting in thin stainless sheet when corrosion resistance is required.
Material	18-8 Stainless: Austenitic 18-8 stainless steel
Hardness	18-8 Stainless: Rockwell B90 - C20 (approx.)
Plating	See Appendix-A for plating information.

Metallics

229 Cross Street
Bristol, CT 06010

www.metallics.us

Phone: 860 589-4186 Toll Free: 800 243-8272

Fax: 860 584-1008 Toll Free Fax: 800 831-9358