


Metallics

An **AMERICAN** Source For Premier
and Innovative Fasteners and Anchors

HEX NYLON INSERT LOCK NUTS – HEAVY HEX, 18-8 STAINLESS STEEL

The following Specification Sheet applies to all **Hex Nylon Insert Lock Nuts – Heavy Hex, 18-8 Stainless Steel** in our **JNYN** series.



Size	C		A		D
	Thickness		Width Across Flats		Hex Height
	Max.	Min.	Max.	Min.	Ref.
1/4	0.390	0.360	0.506	0.489	0.290
5/16	0.453	0.423	0.566	0.551	0.335
3/8	0.562	0.532	0.691	0.675	0.392
7/16	0.609	0.579	0.754	0.736	0.464


Metallics

229 Cross Street
Bristol, CT 06010

www.metallics.us

Phone: 860 589-4186 Toll Free: 800 243-8272

Fax: 860 584-1008 Toll Free Fax: 800 831-9358



Metallics

An **AMERICAN** Source For Premier
and Innovative Fasteners and Anchors

Specification Requirements:

- Dimensions: ASME B18.16.6
- Material: 18-8 Stainless Steel
- Mechanical Properties: Alloy Group 1 Condition CW per ASTM F594 Nylon 6/6 material shall be in compliance with current RoHS European Union Directive
- Performance: Prevailing torque per QA7-95
- Thread Requirements: ASME B1.1, UNC & UNF, Class 2B
- Product Marking: Manufacturer's ID
- Finish: Surface finish per ASTM A380/A380M, and waxed. Wax to contain a tracer element visible under black light. Tracer color to be defined within vendor MTR

Metallics

229 Cross Street
Bristol, CT 06010

www.metallics.us

Phone: 860 589-4186 Toll Free: 800 243-8272

Fax: 860 584-1008 Toll Free Fax: 800 831-9358