




Metallics

An **AMERICAN** Source For Premier
and Innovative Fasteners and Anchors

HEX NYLON INSERT LOCK NUTS –STEEL ZINC

The following Specification Sheet applies to all **Hex Lock Nuts – Steel Zinc** in our **JNYN** series.



Size	C		A		D
	Thickness		Width Across Flats		Hex Height
	Max.	Min.	Max.	Min.	Min.
6	.188	.168	.313	.305	.103
8	.239	.219	.345	.336	.140
10	.249	.229	.376	.367	.140
12	.328	.298	.439	.430	.225
1/4	.328	.298	.439	.430	.225
5/16	.359	.329	.502	.489	.250
3/8	.468	.438	.564	.551	.335
7/16	.468	.438	.627	.616	.324
1/2	.609	.579	.752	.736	.464
5/8	.765	.735	.940	.922	.593
3/4	.890	.860	1.064	1.052	.742

Metallics

229 Cross Street
Bristol, CT 06010

www.metallics.us

Phone: 860 589-4186 Toll Free: 800 243-8272

Fax: 860 584-1008 Toll Free Fax: 800 831-9358



Metallics

An **AMERICAN** Source For Premier
and Innovative Fasteners and Anchors

SPECIFICATION REQUIREMENTS:

- Dimensions: Per ASME B18.16.6
- Material & Mechanical Properties: Nut Material: Carbon Steel, Grade N2 per ASME B18.16.6
Nylon 6/6 material shall be in compliance with current RoHS
European Union Directive
- Performance: Prevailing torque per ASME B18.16.6
- Thread Requirements: ASME B1.1, UNC & UNF, Class 2B
- Finish: Fe/Zn 3AN per ASTM F1941/F1941M

Metallics

229 Cross Street
Bristol, CT 06010

www.metallics.us

Phone: 860 589-4186 Toll Free: 800 243-8272

Fax: 860 584-1008 Toll Free Fax: 800 831-9358