



STRIPE WATER BASED MARKING PAINT

A fast drying marking paint designed to be sprayed in an inverted position. Produces vivid marks, does not clog, and is safe for grass. Meets APWA color standards and is VOC compliant. May be sprayed by hand or with the Z-605 marking gun or Z-606 marking wand.

Suggested Uses:

Utility marking;
Golf courses
Landscaping
Construction sites
Surveying
Mining

Packaging:

Cans per case	12
Shipping Weight	16 ounce cans: 15 lbs., 20 ounce cans: 20 lbs.
Container	16 fluid ounce can, 20 fluid ounce can
Label weight	13 ounces (369 grams), 17 ounces (482 grams)
Hazard Class	2.1
Shipping Classification	Consumer Commodity ORM-D, UN 1950

Properties:

Coverage	Up to 500 linear feet
Cleanup	Paint or lacquer thinner
Flammability	Flammable
Flash point	-4F
Specific Gravity	0.83
Solids Content	26%
MIR value	0.52, cannot exceed 0.85
HAPs content	0
Storage Temperature	40-100F
Application Temperature	50-90F
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years
Freeze/Thaw	Up to 7 times without harm

****Do not warehouse in subfreezing temperatures****

Dry Time*:

To touch	15 minutes @ 72F
	30 minutes @ 35F

****Curing/Recoat time is extended with multiple coats and excessively thick coats****

Gloss for all colors*:	Flat, <15
Gloss for clear*:	high gloss, >80

*as measured on a 60 degree gloss meter

Available Colors:

Description	UPC Code
White	043281000819
Precaution Blue	043281000826 SIMPPB16
Fluorescent Red	043281000833
Safety Green	043281000840 SIMPSG16
Fluorescent Orange	043281000857 SIMPOF16
Fluorescent Red/Orange	043281000864 SIMPROF16
Light Blue	043281000871
Fluorescent Green	043281000888
Fluorescent Blue	043281000895
Alert Orange	043281000901
Safety Red	043281000918 SIMPSR16
Hi Visibility Yellow	043281000925
Caution Yellow	043281000932 SIMPCY16
Fluorescent Hot Pink	043281000949
Clear Line Saver	043281008877