

SPECIFICATIONS



ITEM	DIAMETER	LENGTH	WEIGHT	TENSILE	WORKING LOAD LIMIT
#	INCHES	FEET	LBS	STRENGTH	RANGE -LBS
	1/8	600	3.5	325	27-65
	1/8	3000	10.5	325	27-65
	3/16	600	3.9	650	54-130
	3/16	1200	7.8	650	54-130
	3/16	2400	15.6	650	54-130
	3/16	3600	23.4	650	54-130
M14600	1/4	600	6.9	1125	94-255
M141200	1/4	1200	13.8	1125	94-255
M142400	1/4	2400	27.6	1125	94-255
	1/4	5000	57.5	1125	94-255
	5/16	600	10.8	1710	143-342
	5/16	1200	21.6	1710	143-342
	5/16	2400	43.2	1710	143-342
M38600	3/8	600	15.6	2430	203-486
M381200	3/8	1200	31.2	2430	203-486
	3/8	2400	62.4	2430	203-486
M12600	1/2	600	27.6	3780	315-756
	1/2	1200	55.2	3780	315-756
	5/8	600	43.2	5580	465-1116
	5/8	1200	86.4	5580	465-1116
	3/4	600	62.4	7650	638-1530

ITEM	DIAMETER	LENGTH	WEIGHT	TENSILE	WORKING LOAD LIMIT
	3/4	1200	124.8	7650	638-1530
	1	600	108	12,825	1069-2565
	1	1200	216	12,825	1069-2565
	1 1/8	600	136.8	16,000	1333-3200
	1 1/4	600	165.6	19,350	1613-3870
	1 1/2	600	236.4	27,350	2279-5470