

GROUND CLAMPS Heavy Duty Direct Burial & with Adapters G & G-DB SERIES



EXTRA HEAVY DUTY DIRECT BURIAL



- This incredible ground clamp can handle just about any size ground wire and just about any application.
- UL Listed for direct burial in earth and concrete, be used with rebar, copper water pipe, copper tubing and ground rods up to 1 inch in diameter.
- Assembled with tough 304 stainless steel screws.
- Will accommodate ground wires from 8 AWG to 4/0 AWG.
- cULus Listed 467 Grounding and Bonding.

All dimensional data is listed in inches.

CAT. NO.	PIPE SIZE (IPS)	GROUND WIRE RANGE	REBAR SIZE	GROUND ROD SIZE	LENGTH (L)	WIDTH (W)	HEIGHT (H)	STD. CTN. QTY.
G-140DB	1	8 STR-4/0 STR	3/8-1	1/2-1	2.362	0.669	1.761	10

*Available with silicon bronze screws by adding suffix of -SB.

DIRECT BURIAL WITH WIRE ADAPTERS





- For connecting wire to copper water pipe for grounding.
- Special pressure bar grips cable armor to lessen chances of grounding conductor being pulled out.
- Assembled with silicon bronze screws.
- UL Listed 467 Grounding and Bonding.

APPLICATION:

- UL Listed for direct burial in earth or concrete.



G-20 DB



All dimensional data is listed in inches.

CAT. NO.	PIPE SIZE (IPS)	GROUND WIRE RANGE	GROUND WIRE BOLT SIZE	GROUND CLAMP BOLT SIZE	LENGTH (L)	WIDTH (W)	HEIGHT (H)	STD. CTN. QTY.
G-20 DB	1/2 - 1	4,6,8 STR	1/4 - 20 x 1/2	1/4 - 20 x 1 1/2	2.250	1.000	1.350	20