





Easy-Twist™ Wire Connectors Pails UL486C Listed



- *Flame retardant UL 94V-2 thermoplastic shell provides excellent electrical insulation
- *Temperature rating 105 C (221 F)
- *Fixed, precise square wire spring provides secure gripping of conductors
- *Deep skirt entry provides protection from flashover and shorts
- *Sure-grip ribs improve gripping ability and comfort
- *Compact design ensures proper installation - especially in tight spaces
- *Threaded funnel entry guides the wires into the connector easily
- *Pre-twisting of wires is not necessary
- *1,000 volts maximum in fixtures and signs



Drawn - SD

Approved - KM

Title - Easy-Twist™ Wire Connectors



Catalog Number	Figure	Wire Range	Color	Contents / Qty per Pail	E	A	B	C	D	Temp Rating	Max Voltage	Standard Package Qty
ET-CP-12	1	22-14 AWG	Orange	WC-O 65	.866	.197	.382	.500	.268	105 C	300 V	1
		22-10 AWG	Yellow	WC-Y 45	.969	.236	.433	.551	.268			
		22-10 AWG	Red	WC-R 30	1.043	.339	.516	.642	.406			
		22-8 AWG	Tan	WWC-T 40	1.142	.283	.457	.720	.362			
ET-CP-13	1	22-14 AWG	Orange	WC-O 60	.866	.197	.382	.500	.268	105 C	300 V	1
		22-8 AWG	Tan	WWC-T 45	1.142	.283	.457	.720	.362			
		18-10 AWG	Yellow	WWC-Y 50	1.016	.252	.386	.717	.354			
		18-8 AWG	Red	WWC-R 30	1.252	.354	.512	.906	.378			
ET-CP-14	1	22-14 AWG	Orange	WC-O 65	.866	.197	.382	.500	.268	105 C	600 V 600 V 600 V 300 V	1
		22-10 AWG	Yellow	WC-Y 45	.969	.236	.433	.551	.268			
		22-10 AWG	Red	WC-R 30	1.043	.339	.516	.642	.406			
		22-14 AWG	Blue	WC-B 100	.697	.161	.280	.390	.217			
ET-CP-15	1	22-14 AWG	Grey	WC-G 120	.598	.150	.256	.339	.217	105 C	300 V 300 V 600 V 600 V	1
		22-14 AWG	Blue	WC-B 100	.697	.161	.280	.390	.217			
		22-14 AWG	Orange	WC-O 65	.866	.197	.382	.500	.268			
		22-10 AWG	Yellow	WC-Y 45	.969	.236	.433	.551	.268			