

# 3000 SERIES

## FLUSH MOUNTING LEXAN® HOUSING PHOTOCONTROL



Flush Mounting  
Model 3010



### APPLICATIONS

- Pole lanterns
- Lawn lighting
- Walkways

### SPECIFICATIONS

**ON/OFF:** Turn ON is 1 to 5fc. Turn OFF is 3 to 15fc.

**TIME DELAY:** ON and OFF.

**CELL:** Cadmium sulphide, conformal coated 1/2" diameter.

**CONTACTS:** Normally closed (the unit fails in the ON position).

**LEAD WIRES:** Three color coded, minimum 9" wire leads, #16AWG, rated for 105 °C.

**POWER CONSUMPTION:**  
Averages under 1 watt.

**TEMPERATURE RANGE:**  
-40 °F to +158 °F (-40 °C to +70 °F).

**FAIL MODE:** ON.

**WARRANTY:** 5 years.

### FEATURES

**SENSOR:** Conformal coated cadmium sulphide photocell resists effects of moisture and airborne contaminants. Photocell responds to the light spectrum near to that of a human eye.

**OPERATION:** Delay of up to two minutes to prevent false switching due to light from passing vehicles, lightning, etc.

**STANDARDS:** Meets ANSI/UL773A.

**HOUSING & MOUNTING:** Control housing is weather-resistant molded Lexan® with ultrasonically welded seams.

**MODEL 3000:** Flush mounting through .6875" hole in post lantern or lighting fixture, 3/8" NPT, stem 3/4" long. Gasket and nut supplied.

**MODEL 3010:** flush mounting into standard, raintight junction box. Includes aluminum plate and gasket to fit FS type outdoor junction box.

**ENERGY SAVINGS:** Works with screw base CFLs.

| CAT. NO.         | UPC CODE | VOLTAGE (VAC) 50-60Hz | RATING     |             | LED         |
|------------------|----------|-----------------------|------------|-------------|-------------|
|                  |          |                       | TUNGSTEN   | BALLAST     |             |
| 3000             | 60020    | 120                   | 2000W      | 1800VA      | 600VA       |
| 3002             | 60019    | 208-277               | 3470-4620W | 2080-2770VA | 1040-1385VA |
| <b>NEW!</b> 3006 | 60026    | 347                   | 5760W      | 3470VA      | -           |
| 3010             | 60021    | 120                   | 2000W      | 1800VA      | 600VA       |

\*CSA certified only.

