



Atlanta, Georgia

Phone 800-521-7326

Fax 770-745-1333

Standard Wire Connectors

UL Listed/RoHS Compliant

Temperature Rating - 105 Degrees Celsius (221 Degrees F)

Flame Retardant UL 94V-2 Thermoplastic Shell

Pre-Twisting Of Wire Is Not Necessary

Color	Catalog Number	UPC	Wire Range	Max Voltage	UL Listed	Minimum Wire Range	Maximum Wire Range	Wire Type
Grey	P081G	705591810761	22-14 AWG	300V	UL 486C	2 #22 AWG	1 #14 w/ 1 #20 AWG	Copper Only
Blue	P082B	705591810785	22-14 AWG	300V	UL 486C	2 #22 AWG	3 #16 AWG	Copper Only
Blue	PBP082B	705591812000	22-14 AWG	300V	UL 486C	2 #22 AWG	3 #16 AWG	Copper Only
Orange	P083O	705591810808	22-14 AWG	600V	UL 486C	1 #18 w/ 1 #20 AWG	4 #16 w/ 1 #20 AWG	Copper Only
Orange	PBP083O	705591812024	22-14 AWG	600V	UL 486C	1 #18 w/ 1 #20 AWG	4 #16 w/ 1 #20 AWG	Copper Only
Yellow	P084Y	705591810822	22-10 AWG	600V	UL 486C	3 #20 AWG	1 #10 w/ 2 #14 w/ 1 #16 AWG	Copper Only
Yellow	PBP084Y	705591812048	22-10 AWG	600V	UL 486C	3 #20 AWG	1 #10 w/ 2 #14 w/ 1 #16 AWG	Copper Only
Red	P086R	705591810846	22-8 AWG	600V	UL 486C	3 #18 AWG	3 #10 AWG	Copper Only
Red	PBP086R	705591812062	22-8 AWG	600V	UL 486C	3 #18 AWG	3 #10 AWG	Copper Only

Peco Fasteners specification sheets are a reference guide to help in the selection of fasteners. Peco has made every effort to ensure the accuracy of the information. However, Peco Fasteners is not responsible for any errors that may be contained within these sheets. Peco Fasteners makes no claim of warranty in the accuracy of this information. Users of this information are solely responsible for protecting themselves against liability. It is solely the responsibility of the purchasers and users of these fasteners to consult with Engineers that are experts in an applicable field. Peco Fasteners is not responsible for any loss, claim, or damage due to these specification sheets.

