

GLANDON

Ceiling mounted • Dry location listed **PROGRESS LED**

Project: _____

Fixture Type: _____

Location: _____

Contact: _____

Description:

The 60" Glandon ceiling fan features a 17W LED module (3000K color temperature) with a shatter-proof white opal shade. With a sophisticated and modern design, Glandon has a dual mount system and comes with a full function remote control- batteries are included.

Specifications:

- Antique Nickel (-81) (Painted)
- Steel construction
- White Opal Polycarbonate diffuser
- 60" Glandon indoor ceiling fan features six blades and an LED light source, offering both form and function with energy- and cost-savings benefits
- Shatterproof white opal shade features a dimmable 17W LED module
- Glandon ceiling fan features reversible Walnut/Driftwood blades with an Antique Nickel motor finish
- Beautiful and expansive in design, the 60" Glandon ceiling fan is ideal for use in large indoor spaces, such as great rooms, living rooms and other spacious areas
- A sophisticated and modern design, the 60" Glandon six-blade ceiling fan includes reversible blades that will complement any decor
- Glandon features a dual mount system to offer greater flexibility when installing
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that is larger than 400-square feet
- Reversible motor for year round comfort allows you to choose either a down draft (summer) or an up draft (winter)
- A hand held remote control with fan speed control and full range light dimming is included and comes with a convenient wall bracket for storage
- Remote control may be replaced by a P2630-30 wall control
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 80" of wire supplied
- Walnut/Driftwood reversible blades, plywood construction
- 12 degree blade pitch
- Full Function Remote Included
- Triple capacitor speed control, manual reverse control
- Meets California Title 24 JA8-2016
- Airflow: 5388 CFM*
- Energy consumption: 85 watts (excluding lights)*
- Airflow efficiency: 70 cfm/watt*
- * Fan on a downrod

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1400/82 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-10 °C
Max. Operating Temp	40 °C
Warranty	Limited Lifetime warranty
Labels	ULus Dry location listed
	Meets California Title 24 JA8-2016

For more information visit our website: www.progresslighting.com

P2586-8130K

Images:



Dimensions:

Diameter: 60"
Height: 17-1/8"

Glass
Width: 7-1/4"
Height: 0-7/8"

ENERGYGUIDE

Estimated
Yearly Energy Cost

\$15

Cost Range of Similar Models (19" – 84")

\$3 | | | \$34

• Based on 12 cents per kWh and 6.4 hours use per day
• Your cost depends on rates and use
• Energy Use: 52 Watts

Airflow

3,649

Cubic Feet Per Minute

• The higher the airflow, the more air the fan will move
• Airflow Efficiency: 70 Cubic Feet Per Minute Per Watt

All estimates based on typical use, excluding lights ftc.gov/energy