

## 32" Linear LED Bath

Wall mounted • Damp location listed **PROGRESS LED**

### Description:

Parallel LED bath and vanity fixtures feature a tubular opal glass diffuser paired with a simple, modern oval metal canopy. An integrated LED source provides a variety of energy and cost savings benefits. Suitable for residential and commercial applications, and can be installed vertically or horizontally.

### Specifications:

- Polished Chrome (-015) (plated)
- Steel construction
- Etched White Glass Cylindrical
- A cylindrical design pairs with an oval back plate to create a harmonious design
- 32" linear 50-watt LED bath fixture
- Etched white glass
- Polished Chrome finish
- Integrated LED source provides a variety of energy and cost savings benefits for the homeowner
- Measures 4 3/4" W x 32" H
- 60.3 lumens per watt
- Warm white 3000K lighting color, 3200 lumens and 90+CRI
- Can be mounted on the wall vertically or horizontally
- Modern style and continuous illumination are ideal for a variety of bath and vanity settings - including Mid-Century and Luxe
- Damp location listed
- Dimmable to 10% brightness (See Dimming Notes)
- Backplate covers a standard 4" octagonal recessed outlet box
- Mounting plate for outlet box included
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" - ADA
- Meets California Title 24 JA8-2016

### Performance:

|                     |                                     |
|---------------------|-------------------------------------|
| Number of Modules   | 1                                   |
| Input Power         | 50w                                 |
| Input Voltage       | 120 V                               |
| Input Frequency     | 60 Hz                               |
| Lumens/LPW          | 3200/60.3 (LM-79)                   |
| CCT                 | 3000 K                              |
| CRI                 | 90 CRI                              |
| Life (hours)        | (L70/TM-21)                         |
| FCC                 | Meets FCC Title 47, Part 15 Class B |
| Min. Start Temp     | -10 °C                              |
| Max. Operating Temp |                                     |
| Warranty            | 5-year limited warranty             |
| Labels              | cETLus Damp location listed         |
|                     | Meets California Title 24 JA8-2016  |

**P300184-015-30**

### Images:



### Dimensions:

Width: 4-3/4"  
Depth: 2-3/4"  
Height: 32"  
H/CTR: 2-3/8"

Glass  
Height: 2"

### P300184-015-30

#### Dimming Notes:

---

P300184 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

#### Dimming Controls

---

Lutron - NTELV-300

Lutron - DVELV-300P

Leviton – 6672

Leviton – 6674

Lutron - AYCL-153P

Lutron - TGCL-153-PH-WH

Lutron - AYLV-600P

Lutron - MAELV-601

Leviton - AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.