

## P350085 LED Flush Mount

Ceiling mounted • Damp location listed



### Description:

Featuring a sleek and slim appearance, Bezel LED is an architectural series of flush mount options. Etched white glass is accented by a metal trim in a metallic finish. The glass shade is illuminated on both the bottom and sides to provide a pleasing lighted effect.

### Specifications:

- Brushed Nickel (-009) (plated)
- Steel construction
- Etched white Glass shade
- Features a sleek and slim appearance inspired by architectural design
- One light LED flush mount
- Popular Brushed Nickel finish
- Etched white glass is accented by a metal trim in a metallic finish
- Features 17-watt integrated LED to deliver energy savings and reduce long-term maintenance costs
- The glass shade is illuminated on both the bottom and sides to provide a pleasing lighted effect
- 1276 lumens, 73 lumens per watt
- 3000K color temperature, 90CRI
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

### Performance:

|                     |                                    |
|---------------------|------------------------------------|
| Number of Modules   | 1                                  |
| Input Power         | 17w                                |
| Input Voltage       | 120 V                              |
| Input Frequency     |                                    |
| Lumens/LPW          | 1276/73 (LM-79)                    |
| CCT                 | 3000 K                             |
| CRI                 | 90 CRI                             |
| Life (hours)        | 60,000 (L70/TM-21)                 |
| EMI/RFI             | FCC Title 47, Part 15, Class B     |
| Min. Start Temp     | -30 °C                             |
| Max. Operating Temp | 30°C                               |
| Warranty            | 5 year limited warranty            |
| Labels              | cCSAus Damp location listed        |
|                     | ENERGY STAR® qualified             |
|                     | Meets California Title 24 JA8-2016 |

## P350085-009-30

### Images:



### Dimensions:

Diameter: 10-1/2"

Height: 3-1/2"

Glass

Width: 9-3/4"

Height: 2-1/2"

## P350085 LED Flush Mount

Ceiling mounted • Damp location listed



### P350085-009-30

#### Dimming Notes:

---

P350085 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

#### Dimming Controls

---

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Caseta

Lutron Ariadni AY-600P

Leviton Illumatech IPI06-1LZ

Lutron Lumea LG-603PG

Leviton SureSlide 6672

Leviton SureSlide 6674

Lutron Ariadni AYCL-153P

Lutron Skylark Contour CTCL-153P

Lutron Diva DVCL-153P

Pass & Seymour Harmony DCL453PTCCCV6

Lutron Toggler TGCL-153P

Lutron Maestro MACL-153M

Lutron Ariadni AYLV-600P

Lutron Maestro MA-600

Lutron NOVA T NTLV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Lutron Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.