

ACE LED

Wall mount • Damp location listed



Specifications:

Description:

Two-Light LED modern wall fixture with geometric frosted glass shades. 120V AC replaceable LED module, 623 lumens, 3000K color temperature and 90+ CRI.

Construction:

Polished Chrome (-15) (plated)
 Steel construction
 Etched glass shades
 LED Module is replaceable (part # 93054049)
 Flicker-free dimming to 10% brightness with most ELV type dimmers
 (See Dimming Notes)
 Title 24 compliant
 Back plate covers a standard 4" hexagonal recessed outlet box
 Mounting strap for outlet box included
 Six inches of wire supplied

Performance:

Number of Modules	2
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

P2143-1530K9

Images:



Dimensions:

Width: 15-1/2"
 Height: 4-3/4"
 Depth: 4"
 H/CTR: 2-3/8"

Catalog number:

Base	Finish	Color Temp	CRI
P2143	15 - Polished Chrome	30K - 3000K	9 - 90 CRI

P2143-1530K9

Dimming Notes:

P2143 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.