

# ACE LED

Wall mount • Damp location listed



## Specifications:

### Description:

Three-Light LED modern wall fixture with geometric frosted glass shades. 120V AC replaceable LED module, 623 lumens, 3000K color temperature and 90+ CRI.

### Construction:

Polished Chrome (-15) (plated)  
 Steel construction  
 Etched glass shades  
 LED Module is replaceable (part # 93054049)  
 Flicker-free dimming to 10% brightness with most ELV type dimmers  
 (See Dimming Notes)  
 Title 24 compliant  
 Back plate covers a standard 4" hexagonal recessed outlet box  
 Mounting strap for outlet box included  
 Six inches of wire supplied

### Performance:

|                     |                                                       |
|---------------------|-------------------------------------------------------|
| Number of Modules   | 3                                                     |
| Input Power         | 9W                                                    |
| Input Voltage       | 120V                                                  |
| Input Frequency     | 60Hz                                                  |
| Lumens/LPW          | 623/69.2 (LM-79) per module                           |
| CCT                 | 3000K                                                 |
| CRI                 | 90                                                    |
| Life                | 60,000 (L70/TM-21)                                    |
| EMI/RFI             | FCC Title 47, Part 15, Class B                        |
| Min. Start Temp     | -30° C                                                |
| Max. Operating Temp | 30° C                                                 |
| Warranty            | 5 year warranty                                       |
| Labels              | cCSAus Damp location listed<br>ENERGY STAR® qualified |

## P2144-1530K9

### Images:



### Dimensions:

Width: 24"  
 Height: 4-3/4"  
 Depth: 4"  
 H/CTR: 2-3/8"

### Catalog number:

| Base         | Finish                      | Color Temp         | CRI               |
|--------------|-----------------------------|--------------------|-------------------|
| <b>P2144</b> | <b>15 - Polished Chrome</b> | <b>30K - 3000K</b> | <b>9 - 90 CRI</b> |

## P2144-1530K9

**Dimming Notes:**

P2144 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

**Electronic Low Voltage ELV Reverse Phase Controls**

|         |               |                          |
|---------|---------------|--------------------------|
| Lutron  | Diva Series   | (Part Number DVELV-300P) |
| Lutron  | Nova T Series | (Part Number NTELV-300)  |
| Lutron  | Vierti Series | (Part Number VTELV-600)  |
| Lutron  |               | (Part Number MAELV-600)  |
| Lutron  |               | (Part Number SPELV-600)  |
| Leviton |               | (Part Number AWRMG-EAW)  |
| Leviton |               | (Part Number 6615-P)     |

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.