

TRANSIT

Wall or ceiling mounted • wall or ceiling mounted •

Specifications:

Description:

Transit is a uniquely styled series with clean design flexibility. Can mount to ceiling or wall.
Two-light LED fixture with white acrylic diffuser. 3000K, 90+CRI 1,211 lumens per module.

Construction:

Brushed Nickel (-09) (plated)

Glass: White acrylic diffuser
LED Module is replaceable (part # 93053641)
Flicker-free dimming to 10% brightness with most ELV type dimmers
(See Dimming Notes)
Title 24 compliant
Back plate covers a standard 4" hexagonal recessed outlet box
Mounting strap for outlet box included
6" of wire supplied

Performance:

Number of Modules	2
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1211/71.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus ENERGY STAR® qualified

P3417-0930K9

Images:



Dimensions:

Square: 14"
Height: 3-3/4"
Depth: 3-3/4"
H/CTR: 7"

Catalog number:

Base	Finish	Color Temp	CRI
P3417	09 - Brushed Nickel	30K - 3000K	9 - 90 CRI

P3417-0930K9

Dimming Notes:

P3417 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.