

LED FLUSH

Ceiling mounted • Damp location listed



Specifications:

P350054-009-30

Description:

One-light LED Flush Mount

Construction:

- Brushed Nickel (-009)
- Steel construction
- Glass: Etched glass bowl
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- Unit covers a standard 4" hexagonal recessed outlet box
- Mounting plate for outlet box included
- 6" of wire supplied
- Brushed Nickel finish
- 120V AC replaceable module
- Dimmable to 10% with Triac or ELV dimmers
- 3000k color temperature
- TM-21 60,000 hour life

Performance:

Number of Modules	1
Input Power	24W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	2015/83.95833333 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

Images:



Dimensions:

Diameter: 13-1/4"

Height: 4-3/4"

Catalog number:

Base	Finish	Color Temp	CRI
P350054	009 - Brushed Nickel	30	Blank- 90 CRI