

# PORTAL

Ceiling mount • Damp location listed



## Specifications:

### Description:

The P3632 features a 120V alternating current (AC) source which eliminates the need for a traditional LED driver.

### Construction:

Brushed Nickel (-09) (plated)  
 Steel construction  
 LED Module is replaceable (part #)  
 Flicker-free dimming to 10% brightness with most ELV type dimmers  
 (See Dimming Notes)  
 Title 24 compliant  
 Chassis covers a standard 4" hexagonal recessed outlet box  
 Mounting strap for outlet box included  
 Six inches of wire supplied

### Performance:

|                     |                                                       |
|---------------------|-------------------------------------------------------|
| Number of Modules   | 1                                                     |
| Input Power         | 29W                                                   |
| Input Voltage       | 120V                                                  |
| Input Frequency     | 60Hz                                                  |
| Lumens/LPW          | 2197/75.8 (LM-79) per module                          |
| CCT                 | 3000K                                                 |
| CRI                 | 90+                                                   |
| Life                | 60000 (L70/TM-21)                                     |
| EMI/RFI             | FCC Title 47, Part 15, Class B                        |
| Min. Start Temp     | -30° C                                                |
| Max. Operating Temp | 30° C                                                 |
| Warranty            | 5 year warranty                                       |
| Labels              | cCSAus Damp location listed<br>ENERGY STAR® qualified |


## P3632-0930K9

### Images:



### Dimensions:

Diameter: 13"  
 Height: 2-1/2"



### Catalog number:

| Base         | Finish                     | Color Temp         | CRI                |
|--------------|----------------------------|--------------------|--------------------|
| <b>P3632</b> | <b>09</b> - Brushed Nickel | <b>30K</b> - 3000K | <b>9</b> - 90+ CRI |

P3632-0930K9

Dimming Notes:

P3632 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

|         |               |                          |
|---------|---------------|--------------------------|
| Lutron  | Diva Series   | (Part Number DVELV-300P) |
| Lutron  | Nova T Series | (Part Number NTELV-300)  |
| Lutron  | Vierti Series | (Part Number VTELV-600)  |
| Lutron  |               | (Part Number MAELV-600)  |
| Lutron  |               | (Part Number SPELV-600)  |
| Leviton |               | (Part Number AWRMG-EAW)  |
| Leviton |               | (Part Number 6615-P)     |

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.  
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.